

STATE OF INDIANA
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF WATER
INDIANAPOLIS, INDIANA

GEODETTIC CONTROL DATA

Benchmark Descriptions
And Elevations

MARION COUNTY

The layout, surveys, adjustments, and publication of the following level lines have been developed by the staff of the Department of Natural Resources. The monumentation, field surveys, and adjustments were conducted between 1952 and 1991. This publication is based on an extensive recovery program conducted in the 1980's by the Surveying and Mapping Section. It replaces the October 5, 1964 publication of the Indiana Flood Control and Water Resources Commission. All field survey records and publication procedures in the process of development of this list may be examined at the office of the Department of Natural Resources in Indianapolis, Indiana. All elevations published to the nearest one-onethousandth of a foot are based on second order or higher order leveling. All elevations published to the nearest one-onehundredth of a foot are based on third order leveling. Requests for specific information pertaining to the surveys in this county, or others in the state, are accepted as a public service.

June 1991

STATE OF INDIANA
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF WATER
INDEX TO MARION COUNTY BENCHMARKS

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR BM	UNSTAMPED	792.299	Page 2
DNR BM	MAR 1-8783	759.61	Page 23
DNR BM	MAR 2 RESET	802.028	Page 65
DNR BM	MAR 3	800.957	Page 65
DNR BM	MAR 7 RESET	795.305	Page 19
DNR BM	MAR 8 RESET	757.859	Page 17
DNR BM	MAR 10	742.675	Page 19
DNR BM	MAR 12 RESET	730.215	Page 17
DNR BM	MAR 14	717.670	Page 34
DNR BM	MAR 16	715.058	Page 34
DNR BM	MAR 17	710.882	Page 34
DNR BM	MAR 19	711.082	Page 34
DNR BM	MAR 20 RESET	701.190	Page 39
DNR BM	MAR 23	691.782	Page 50
DNR BM	MAR 25	711.264	Page 35
DNR BM	MAR 26	711.442	Page 35
DNR BM	MAR 28	718.584	Page 35
DNR BM	MAR 29	715.340	Page 35
DNR BM	MAR 31	715.419	Page 35
DNR BM	MAR 36	734.285	Page 36
DNR BM	MAR 38	726.399	Page 24
DNR BM	MAR 40	743.099	Page 24

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR BM	MAR 42 RESET	761.366	Page 24
DNR BM	MAR 43	769.422	Page 21
DNR BM	MAR 49 RESET	689.386	Page 50
DNR BM	MAR 50	697.355	Page 50
DNR BM	MAR 52	702.745	Page 36
DNR BM	MAR 54	704.907	Page 36
DNR BM	MAR 55	704.885	Page 36
DNR BM	MAR 58	700.343	Page 37
DNR BM	MAR 60	713.269	Page 37
DNR BM	MAR 61 RESET	695.555	Page 38
DNR BM	MAR 62 RESET	696.082	Page 43
DNR BM	MAR 63	716.294	Page 43
DNR BM	MAR 69	707.185	Page 40
DNR BM	MAR 72 RESET	725.614	Page 40
DNR BM	MAR 73 RESET	710.698	Page 49A
DNR BM	MAR 78	734.944	Page 39
DNR BM	MAR 80	720.028	Page 10
DNR BM	MAR 81	717.895	Page 15
DNR BM	MAR 82	729.765	Page 10
DNR BM	MAR 91	798.621	Page 64
DNR BM	MAR 92	794.701	Page 64
DNR BM	MAR 93	798.546	Page 64
DNR BM	MAR 96	688.264	Page 51
DNR BM	MAR 97	687.735	Page 51
DNR BM	MAR 101	729.840	Page 57
DNR BM	MAR 106	767.976	Page 4
DNR BM	MAR 110	676.901	Page 51

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR BM	MAR 112	730.036	Page 17
DNR BM	MAR 115	781.432	Page 1
DNR BM	MAR 117	786.034	Page 1
DNR BM	MAR 118	796.005	Page 2
DNR BM	MAR 126	725.052	Page 42
DNR BM	MAR 127	761.552	Page 24
DNR BM	MAR 128	762.025	Page 25
DNR BM	MAR 129	776.462	Page 24
DNR BM	MAR 130	784.027	Page 26
DNR BM	MAR 131	783.313	Page 26
DNR BM	MAR 132	798.486	Page 27
DNR BM	MAR 133	790.263	Page 27
DNR BM	MAR 137	813.655	Page 30
DNR BM	MAR 138	828.709	Page 29
DNR BM	MAR 139	835.738	Page 31
DNR BM	MAR 140	760.064	Page 29
DNR BM	MAR 141	759.733	Page 28
DNR BM	MAR 143	733.986	Page 4
DNR BM	MAR 144	730.876	Page 56
DNR BM	MAR 145	725.085	Page 56
DNR BM	MAR 148	717.272	Page 55
DNR BM	MAR 149	709.874	Page 55
DNR BM	MAR 151	695.043	Page 53
DNR BM	MAR 152	680.791	Page 53
DNR BM	MAR 153	687.751	Page 53
DNR BM	MAR 154	682.059	Page 52

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR BM	MAR 155	695.825	Page 52
DNR BM	MAR 157	741.502	Page 38
DNR BM	MAR 160	744.160	Page 43
DNR BM	MAR 162	757.242	Page 44
DNR BM	MAR 164	799.960	Page 44
DNR BM	MAR 165	743.013	Page 44
DNR BM	MAR 167	747.145	Page 45
DNR BM	MAR 170	799.708	Page 19
DNR BM	MAR 173	754.612	Page 8
DNR BM	MAR 176	781.736	Page 19
DNR BM	MAR 178	805.638	Page 18
DNR BM	MAR 250	792.096	Page 13
DNR BM	MAR 251	809.760	Page 13
DNR BM	MAR 252	733.727	Page 14
DNR STA	CCA A1	896.457	Page 11
DNR STA	CCA A2	849.419	Page 12
DNR STA	CCA A3	812.724	Page 12
DNR STA	CCA A4	791.586	Page 12
DNR STA	CCA A5	781.01	Page 47
DNR STA	CCA A6	774.61	Page 47
DNR STA	CCA C1	733.07	Page 46
DNR STA	CCA C2	774.49	Page 46
DNR STA	CCA C3	774.44	Page 46
DNR STA	CCA D1	708.75	Page 47
DNR STA	CCA D2	751.09	Page 47
DNR STA	FIE C7	735.776	Page 32

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR STA	FIE C3	736.337	Page 31
DNR STA	FIE C17	749.444	Page 32
DNR STA	FIE E22	752.551	Page 32
DNR STA	FIE E6	834.994	Page 64
DNR STA	FIE F2	841.536	Page 64
DNR STA	FIW A6	739.146	Page 47
DNR STA	LBI 11 A	734.188	Page 59
DNR STA	LBI 14 A	722.652	Page 59
DNR STA	LBI 4 A	748.949	Page 59
DNR STA	LBI 8 A	740.147	Page 59
DNR STA	LBI 11 B	792.804	Page 5
DNR STA	LBI 18 B	777.869	Page 6
DNR STA	LEA B1	716.59	Page 45
DNR STA	LEA B2	721.21	Page 45
DNR STA	LEA B3	734.90	Page 45
DNR STA	LEA B4	740.33	Page 45
DNR STA	LEA B5	786.12	Page 46
DNR STA	LEA B6	795.16	Page 46
DNR STA	LEA B7 RESET	808.19	Page 19
DNR STA	LEA B8	830.40	Page 12
DNR STA	LEA B9	851.53	Page 11
DNR STA	LI TT A18	844.109	Page 33
DNR STA	LI TT A26	861.264	Page 33
DNR STA	LI TT A12	802.597	Page 6
DNR STA	LI TT A16	791.771	Page 5
DNR STA	LI TT A7	720.911	Page 58

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR STA	LI TT A8	715.300	Page 58
DNR STA	LI TT A9	732.012	Page 59
DNR STA	PRG A3	818.174	Page 6
DNR STA	PRG A5	815.165	Page 7
DNR STA	TT A1	783.909	Page 22
DNR STA	TT A10	726.201	Page 16
DNR STA	TT A12	763.431	Page 11
DNR STA	TT A13	765.453	Page 11
DNR STA	TT A2	753.081	Page 22
DNR STA	TT A4	731.450	Page 23
DNR STA	TT A6	723.053	Page 10
DNR STA	TT A7	738.737	Page 48
DNR STA	TT A8	725.874	Page 48
DNR STA	TT A9	726.926	Page 16
DNR STA	TT A15	737.807	Page 23A
DNR STA	TT A17	733.308	Page 23A
DNR STA	TT B3	734.041	Page 23
DNR STA	TT C2	790.770	Page 48
DNR STA	TT C3	771.803	Page 48
DNR STA	TT C4	772.819	Page 48
DNR STA	TT C6	750.493	Page 49
DNR STA	TT C7	761.513	Page 49
DNR STA	TT C8	739.978	Page 49
DNR STA	TT C10	717.490	Page 49
DNR STA	WHSI TT 2D	689.067	Page 61
DNR STA	WHSI TT 2F	660.092	Page 62

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR STA	WHSI TT 10C	691.996	Page 61
DNR STA	WHSI TT 14D	687.422	Page 61
DNR STA	WHSI TT 1N	689.810	Page 63
DNR STA	WHSI TT 21E	695.203	Page 61
DNR STA	WHSI TT 24E	703.113	Page 62
DNR STA	WHSI TT 26E	703.612	Page 62
DNR STA	WHSI TT 2G	657.343	Page 63
DNR STA	WHSI TT 3N	671.424	Page 63
DNR STA	WHSI TT 3P	684.402	Page 63
DNR STA	WHSI TT 6A	686.053	Page 60
DNR STA	WHSI TT 6C	687.432	Page 61
DNR STA	WHSI TT 9A	697.302	Page 60
DNR STA	WRSI TT 11A	676.120	Page 60
DNR STA	WRSI TT 13A	677.846	Page 60
DNR STA	WRSI TT 14A	677.260	Page 60
DNR TBM	1	731.133	Page 17
DNR TBM	A	718.747	Page 17
DNR TBM	A	751.260	Page 57
DNR TBM	B	751.144	Page 57
DNR TBM	B	765.808	Page 22
DNR TBM	BC 27	813.664	Page 3A
DNR TBM	BC 30	830.396	Page 2
DNR TBM	BC 31	801.841	Page 3
DNR TBM	BC 32	843.343	Page 3
DNR TBM	BC 34	835.275	Page 20
DNR TBM	BC 35	820.129	Page 20

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR TBM	DRC 1	720.125	Page 42
DNR TBM	DRC 2	725.536	Page 42
DNR TBM	DRC 3	727.097	Page 42
DNR TBM	DRC 5	732.178	Page 41
DNR TBM	DRC 8	741.499	Page 38
DNR TBM	E 6	836.411	Page 65
DNR TBM	EFWL 12	754.126	Page 8
DNR TBM	EFWL 13	762.095	Page 18
DNR TBM	EFWL 15	801.340	Page 18
DNR TBM	F 2	840.559	Page 21
DNR TBM	FC 2	736.685	Page 44
DNR TBM	GC 1	683.334	Page 53
DNR TBM	GC 1	728.000	Page 8
DNR TBM	HD 1	697.984	Page 52
DNR TBM	LBC 3	689.985	Page 51
DNR TBM	LBC 10	767.916	Page 4
DNR TBM	LBC 11	760.358	Page 4
DNR TBM	LBC 17	851.457	Page 5
DNR TBM	LBC 18	744.065	Page 56
DNR TBM	LBC 19	751.404	Page 56
DNR TBM	LEC 1	718.176	Page 40
DNR TBM	LEC 4	719.964	Page 41
DNR TBM	LEC 6	748.019	Page 43
DNR TBM	LEC 7	756.077	Page 43
DNR TBM	MD 2	744.683	Page 38
DNR TBM	PIVOT POINT 1	723.405	Page 14

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR TBM	PIVOT POINT 4	824.280	Page 15
DNR TBM	PIVOT POINT 5	826.703	Page 15
DNR TBM	PIVOT POINT 6	827.539	Page 15
DNR TBM	PR 1	764.796	Page 25
DNR TBM	PR 2	768.017	Page 26
DNR TBM	PR 3	805.057	Page 29
DNR TBM	PR 4	815.104	Page 29
DNR TBM	PR 5	823.430	Page 29
DNR TBM	PR 8	842.143	Page 30
DNR TBM	PR 9	844.641	Page 30
DNR TBM	PR 10	862.364	Page 31
DNR TBM	PR 11	778.451	Page 28
DNR TBM	PR 13	743.898	Page 28
DNR TBM	PR 14	743.858	Page 28
DNR TBM	PR 15	738.423	Page 28
DNR TBM	PR 17	734.330	Page 57
DNR TBM	PR 19	720.804	Page 55
DNR TBM	PR 20	708.342	Page 55
DNR TBM	PR 21	706.056	Page 55
DNR TBM	PR 22	707.720	Page 54
DNR TBM	PR 25	691.973	Page 54
DNR TBM	PR 26	692.431	Page 54
DNR TBM	PR 27	712.588	Page 55
DNR TBM	TT A10	726.201	Page 16
DNR TBM	TT A9	726.926	Page 16
DNR TBM	W 51	722.630	Page 10

AGENCY	DESIGNATION	ELEVATION	PAGE
DNR TBM	W 52	731.283	Page 10
DNR TBM	WC 5	798.862	Page 13
DNR TBM	WC 6	761.594	Page 13
DNR TBM	WC 7	737.695	Page 14
DNR TBM	WC 8	715.786	Page 13
DNR TBM	WHR 209	698.804	Page 58
DNR TBM	WHR 211	690.288	Page 58
DNR TBM	WR 200	717.898	Page 8
DNR TBM	WR 201	703.232	Page 50
INDOT BM	HAM C44	809.083	Page 14
INDOT BM	MAR 0102	768.947	Page 18
INDOT BM	MAR 35	726.866	Page 41
INDOT BM	MAR G 10	733.289	Page 22
INDOT BM	MAR G 19	723.247	Page 42
INDOT BM	MAR G 20	722.140	Page 40
INDOT BM	MAR G 26	823.646	Page 65
INDOT BM	MAR G 27	713.089	Page 37
INDOT BM	MAR G 29	828.815	Page 30
INDOT BM	MAR G 45	701.086	Page 54
INDOT BM	MAR G 46	783.431	Page 1
INDOT BM	MAR G 98	753.021	Page 57
INDOT BM	MAR G132	754.790	Page 14
INDOT BM	MAR G3	750.829	Page 9
INDOT BM	MARG 357	764.14	Page 23
NGS BM	A 14	726.960	Page 52
NGS BM	B 238	856.147	Page 20

AGENCY	DESIGNATION	ELEVATION	PAGE
NGS BM	B 43	736.931	Page 39
NGS BM	B 77	794.788	Page 18
NGS BM	D 238	828.496	Page 20
NGS BM	D 43	736.613	Page 36
NGS BM	D 79	714.300	Page 34
NGS BM	E 237	767.774	Page 22
NGS BM	E 79	715.756	Page 37
NGS BM	H 79	711.839	Page 37
NGS BM	J 238	811.599	Page 3A
NGS BM	K 238	812.193	Page 2
NGS BM	M 238	796.481	Page 1
NGS BM	Q 64	694.438	Page 50
NGS BM	S 245	851.809	Page 6
NGS BM	T245 RESET	853.329	Page 6
NGS BM	W 236	760.090	Page 21
NGS BM	X 78	761.547	Page 34
NGS BM	Y 242	782.551	Page 26
NGS BM	Z 235	880.248	Page 31
NGS BM	Z 242	818.102	Page 26
NGS BM	Z 245	761.960	Page 27
USED TBM	10	703.640	Page 36
USED TBM	14	696.671	Page 37
USED TBM	19	716.063	Page 40
USED TBM	39	724.221	Page 39
USED TBM	42	724.009	Page 10
USGS	RM 1	688.166	Page 54

AGENCY	DESIGNATION	ELEVATION	PAGE
USGS	RM 1	766.047	Page 21
USGS	RM 1	767.548	Page 25
USGS	RM 1	798.868	Page 27
USGS	RM 2	727.870	Page 41
USGS	RM 2	767.527	Page 25
USGS	RM 2	800.70	Page 27
USGS	RM 3	721.725	Page 41
USGS	RM 3	765.997	Page 21
USGS	RM 3	766.864	Page 25
USGS	RM 5	716.256	Page 39
USGS	RP	831.353	Page 30
USGS BM	112 M	858.505	Page 5
USGS BM	113 M	665.002	Page 62
USGS BM	114 M	705.794	Page 58
USGS BM	116 M	721.634	Page 62
USGS BM	TT 8 DWP	718.518	Page 35
USGS TBM	83/LI	676.038	Page 8

MARION COUNTY
ACTON QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 115	In Marion County, SE 1/4 Sec. 15, T.14N, R.5E. About 0.55 mile northeast of Acton, 0.78 mile generally east along McGregor Road from its intersection with Acton Road at Acton to the McGregor Road bridge over Buck Creek, 0.04 mile west of the junction of Dix and McGregor Roads, at the northeast corner of the bridge, set in the top at the east end of the north side of the north concrete sidewalk, 17 feet north of the centerline of the road, 14.5 feet west of the east end of the north sidewalk, 2.7 feet below the northeast end of the north aluminum handrail, 0.3 foot east of the west face of the east abutment, a standard Indiana Flood Control and Water Resources Commission bronze benchmark, stamped "MAR 115 1959." 781.432
NGS BM M 238	In Marion County, SE 1/4 Sec. 10, T.14N, R.5E. About 1.3 miles northeast of Acton, at the intersection of the Shelby-Marion County Line Road and U.S. Highway 421, in the southwest quarter of the intersection, set in the top of a concrete post projecting 0.5 foot above the ground, 34 feet southwest of the centerline of U.S. 421, 14.5 feet west of the centerline of the County Line Road, 10 feet south of a fence corner, 1.5 feet east of a fence line, 1.0 foot below the highway level, a standard USC & GS benchmark tablet, stamped "M 238 1947" 796.481
INDOT BM MAR G 46	In Marion County, N.1/2 Sec. 10, T.14N, R.5E. About 1.5 miles north of Acton, 0.7 mile northwest along U.S. Highway 421 from its intersection with the Shelby-Marion County Line and Road, at the U.S. 421 bridges over Buck Creek, at the center bridge, set in the top at the northwest end of the northeast guardrail base, 19.5 feet northeast of the center line of the road, 0.7 foot above the roadway, 0.2 foot southeast of the northwest end of the northeast guardrail base, a standard ISHC benchmark tablet, stamped "MAR G 46." 783.431
DNR BM MAR 117	In Marion County, SW 1/4 Sec. 34, T.15N, R.5E. About 2.95 miles north of Acton, 1.62 miles northwest along U.S. Highway 421 from its intersection with the Shelby-Marion County Line and Road to a T-road north (Senour Road), thence 0.88 mile north along Senour Road to an east-west crossroad (Thompson Road to the Thompson Road bridge over Buck Creek, set in the top of the north end of the east bridge seat, 17 feet north of the center line of the road, 3 feet below the roadway, 1.5 feet east of the west face of the east bridge seat, 0.3 foot south of the north edge of the bridge seat, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 117 1959." 786.034

MARION COUNTY
ACTON QUAD

MARK	ELEVATION FEET (NGVD 29)
NGS BM K 238	<p>In Marion County, NE 1/4 Sec. 3, T.14N, R.5E. About 3.05 miles northeast of Acton, 1.9 miles north along the Shelby-Marion County Line Road from its intersection with U.S. Highway 421 to a crossroad (Thompson Road) at the southwest corner of Hancock County, at the northwest corner of Shelby County, in the southwest quarter of the offset intersection, 54 feet north of a power pole, set in the top of a concrete post projecting 0.5 foot above the ground, 37 feet south of the centerline of Thompson Road, 21 feet west of the centerline of the County Line Road, 20 feet south of a fence corner, 1.0 foot east of a fence line, 1.0 foot above the ground a standard USC & GS benchmark tablet, stamped "K 238 1947."</p> <p style="text-align: right;">812.193</p>
DNR BM MAR 118	<p>In Marion County, W. 1/2 Sec. 34, T.15N, R.5E. About 3.4 miles north of Acton, 2.4 miles north along the Shelby-Marion and Hancock-Marion County Line Road from its intersection with U.S. Highway 421 to a T road west (Pentecost Road), thence 0.7 mile west along Pentecost Road to the Pentecost Road bridge over Buck Creek, set in the top at the east end of the south walkway of the bridge, 17 feet south of the centerline of the road, 0.9 foot above the roadway, 0.6 foot northwest of the southeast end of the south walkway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 118 1959."</p> <p style="text-align: right;">796.005</p>
DNR BM UNSTAMPED	<p>In Marion County, W. 1/2 Sec. 34, T.15N, R.5E. About 3/4 miles north of Acton, 2.4 miles north along Shelby-Marion and Hancock-Marion County Line Road from its intersection with U.S. Highway 421 to a T-road west (Pentecost Road), thence 0.7 mile west along Pentecost Road to the Pentecost Road bridge over Buck Creek, set in the top of the north end of the east bridge seat, 17 feet north of the centerline of the road, 3 feet below the roadway, 0.4 foot east of the west face of the east abutment, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, not stamped.</p> <p style="text-align: right;">792.299</p>
DNR TBM BC 30	<p>In Marion County E. 1/2 Sec. 28, T.15N, R.5E. About 4.1 miles south of Cumberland, 4.14 miles south along the Hancock-Marion County Line Road from its junction with U.S. Highway 40 at the east edge of Cumberland to an offset crossroad (Vandergriff Road), thence 1.25 miles west along Vandergriff Road to a crossroad (Senour Road), in the southwest quarter of the junction, set in the east side of a telephone pole Number 3512, 14 feet west of the centerline of the north-south road, 13 feet south of the extended centerline of the road leading east, 0.5 foot above the ground, about level with the road, a railroad spike driven through an aluminum tag, stamped "TBM BC 30 1959".</p> <p style="text-align: right;">830.396</p>

MARION COUNTY
ACTON QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM BC 31	In Marion County, SE 1/4 Sec. 21, T.15N, R.5E. About 3.5 miles south of Cumberland, 2.95 miles south along the Hancock-Marion County Line Road from its junction with U.S. Highway 40 at the east edge of Cumberland to a crossroad (U.S. 52), thence 0.45 mile northwest along U.S. 52 to a T-road south (Kitley Road), thence 0.67 mile south along Kitley to a T-road west (Troy Avenue), thence 0.6 mile west along Troy Avenue to the Troy Avenue bridge over Buck Creek, set in the top of the northwest wingwall of the bridge, 14 feet north of the centerline of the road, 3 feet below the top of the north guardrail, 0.8 foot north of the north face of the north guardrail, 0.7 foot east of the west face of the wingwall, a chiseled triangle. 801.841
DNR TBM BC 32	In Marion County, E. 1/2 Sec. 21, T.15N, R.5E. About 3.1 miles southwest of Cumberland, 2.94 miles south along the Hancock-Marion County Line Road from its junction with U.S. Highway 40 at the east edge of Cumberland to a crossroad (U.S. 52), thence 1.43 miles northwest along U.S. 52 to a T-road south (Senour Road), thence 0.45 mile south along Senour Road to a house on the west side of the road, set in the northwest side of a 22 inch maple tree, 55 feet northwest of a telephone pole Number 6, 13 feet east of the centerline of the road, 8 feet north of the centerline of the north entrance drive to the house, 0.2 feet above the roadway, a railroad spike driven through an aluminum tag, stamped "TBM BC 32 1959". 843.343

MARION COUNTY
ACTON QUAD

MARK		ELEVATION FEET (NGVD 29)
DNR TBM BC 27 1959	In Hancock County, Acton Quad, near the W/ corner Sec. 35, T.15N, R.5E, at the intersection of Marlin Road and Marion and Hancock County line Road. Set in the NE/ of the intersection, 15 feet east of the centerline of county line road, 11 feet north of the centerline of Marlin Road, 0.5 feet above the ground and about level with the roadway, set in the west side of power pole #50-0-HAN 6, a railroad spike driven through an aluminum tag, stamped "TBM BC 27 1959."	813.664
NGS BM J 238 1947	In Hancock County, Acton Quad, near the SW corner of Sec. 26, T.15N, R.5E, about 1.5 miles south of the intersection of U.S. Highway 52 and Marion & Hancock County line road, along said county line road. About 180 feet north of the south section line, about 180 feet north of a field entrance east, about 115 feet north of a power pole #69-0-HAN. 6, 72 feet south of a power pole #71-0-HAN. 6, 19 feet east of the centerline of the County line road, 15 feet south of a dead 28-inch tree stump (about 10 feet high), 1.0 foot west of a fence line, set in the top of a concrete post projecting 5 inches above the ground, a standard USC&GS bench mark tablet, stamped "J 238 1947."	811.599

MARION COUNTY
BEECH GROVE QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM LBC 11	In Marion County, SW 1/4 Sec. 8, T.14N, R.4E. About 0.7 mile northeast of Southport, 0.75 mile east along Southport Road (Union Street) from its intersection with the State Road 431 in Southport to a T road north, thence 0.1 mile north along the narrow gravel road to a wooden bridge over Little Buck Creek, set in the northwest side of a 36 inch willow tree at the south-east corner of the bridge, 27 feet northeast from a power pole #77E-760, 6 feet east from the centerline of the road, 4 feet south from the south end of the bridge, 0.7 foot above the ground, a railroad spike driven vertically through a brass plate, stamped "TBM LBC 11 1956". 760.358
DNR TBM LBC 10	In Marion County, S. 1/2 Sec. 8, T.14N, R.4E. About 0.9 mile east of Southport, 0.9 mile east along Southport Road (Union Street) from its intersection with State Road 431 in Southport to the intersection of McFarland Road, thence 0.05 mile north to the McFarland Road concrete bridge over Little Buck Creek, set in the top of the south end of the east concrete guardrail, 13 feet east from the centerline of the road, 2.8 feet above the road, 1.1 feet north from the south end of the east concrete guardrail, a chiseled square. 767.916
DNR BM MAR 106	In Marion County, S. 1/2 Sec. 8, T.14N, R.4E. About 0.9 mile east of Southport, 0.9 mile east along Southport Road (Union Street) from its intersection with State Road 431 in Southport to the intersection of McFarland Road, thence 0.05 mile north to the McFarland Road concrete bridge over Little Buck Creek, set in the top of the north end of the east concrete guardrail, 13 feet east from the centerline of the road, 9.3 feet south from the north end of the east concrete guardrail, 2.8 feet above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 106 1956". 767.976
DNR BM MAR 143	In Marion County, NE 1/4 Sec. 18, T.15N, R.4E. At Indianapolis, at the Churchman Avenue bridge over Pleasant Run, set in the west of the centerline of the road, 17.9 feet south of the north end of the west guardrail, 0.3 foot above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 143 1960". 733.986

MARION COUNTY
BEECH GROVE QUAD

ELEVATION
FEET
(NGVD 29)

MARK

USGS BM 112 M	In Marion County, SW 1/4 Sec. 36, T.15N, R.4E. About 5 miles northeast of Southport, 2.5 miles east along Southport Road from its intersection with Madison Ave. in Southport to the intersection of Emerson Avenue, thence 2.1 miles north along Emerson Ave. to the intersection of Thompson Rd., thence 2.3 miles E. along Thompson Rd. to a farm drive leading north to two white houses, in the NW corner of the junction, set in the top of a concrete post projecting 0.2 ft. above the ground, 29.5 ft. NW from a mail box; 24 feet north from the centerline of Thompson Rd.; 6 ft W. of the centerline of the farm drive, a standard USGS benchmark tablet, stamped "112 M 1945". 858.505
DNR TBM LBC 17	In Marion County, NE 1/4 Sec. 1, T.14N, R.4E. About 5.7 miles northeast of Southport, 2.45 miles east along Union Street (Southport Road) from its intersection with State Road 431 in Southport to the intersection of Emerson Avenue, thence 2.05 miles north along Emerson Avenue to the intersection of Thompson Road, thence 2.90 miles east along Thompson Road to the crossing of the New York Central Railroad, in the southeast corner of the crossing, set in the top of the northeast end of the southeast abutment, 209 feet south from the centerline of Thompson Road, 11 feet northeast from the northeast rail, a 0.1 foot round bolt head. 851.457
DNR STA LI TT A16	In Marion County, SE 1/4 Sec. 16, T15N, R4E, From the intersection of south Emerson Avenue and Southeastern Ave. proceed south on Emerson for 0.2 miles to the mark located on west side of the street, and just south of asphalt drive into apartments. 46.8 feet east of 10" sweet-gum tree 23.0 feet south of centerline of asphalt road leading to apartments, and 14.2 feet west of centerline of Emerson Avenue. A bronze disk in a conc. post. 791.771
DNR STA LBI 11B	In Marion County, SW 1/4 Sec. 10, T14N, R4E. About 2.4 miles east of Southport, 2.4 miles east along southport Road from its intersection with S.R. 431 (Madison Ave.) in Southport to the intersection of Emerson Ave, thence north 0.15 mile north of Southport Rd. to a standard Indiana Department of Natural Resources bronze tablet set in top of 1'by 1' concrete monument flush with the ground on the east side of Emerson Ave. 200' south of bridge over Little Buck Creek. 2.5' E. of a power pole. Stamped "LBI 11B" and about 350 ft. south from centerline of 3 span conc. bridge over Buck Creek. 792.804

MARION COUNTY
BEECH GROVE QUAD

ELEVATION
FEET
(NGVD 29)

MARK

DNR STA In Marion County, SW Sec. 8, T14N, R4E. About 0.7 mile east
LBI 18B of Southport, 0.7 mile east along Southport Rd. from its inter-
section with S.R. 431 (Madison Ave.) to a standard IDNR bronze
tablet set in a 1' by 1' concrete monument flush with the
ground, at the N.E. corner of the intersection of Pine St. and
Southport Rd. 23' north of Southport Rd., 8.4' feet south of the
southwest cor. of a chain link fence for a church parking, near
the S.E. corner of a cemetery. Stamped "LBI 18B". 777.869

DNR STA In Marion County, SW Sec. 21, T14N, R4E., From the Circle
PRG A3 at Indianapolis, thence 9.7 miles Southerly to the Intersection
of Madison and County Line Road; thence East on County Line Road
for 1.1 miles to a standard Indiana Department of Natural Re-
sources bronze tablet set in a 6" x 6" concrete monument on the
north side of the road. About 50 feet east of a single story
gray house (#4084) of C. G. Wheatcraft; about 0.15 miles East
of Sherman Drive; 9.5 ft. north of the north edge of the county
road; and 16 ft. east of the centerline of a driveway to the
north. 818.174

NGS BM In Marion Co., NE 1/4 Sec. 1, T14N, R4E, About 5.7 Miles NE
T 245 of Southport. From the intersection of Emerson Ave. and
RESET Thompson Rd. go 2.9 mi. E. on Thompson Rd. to it's intersection
with the Conrail tracks and the mark in the SE corner of the
crossing; 198' S of the centerline of Thompson Rd., and 10.6'
NE of the NE rail. Set in the top of the NW end of the NE
headwall of a 10' box culvert. A standard USC&GS BM tablet
stamped "T 245 1947" 853.329

NGS BM In Marion Co., W 1/2 Sec. 6, T14N, R5E, About 6.1 Miles NE of
S 245 Southport. From the intersection of Franklin Rd. and Southport
Road go 1.5 miles north on Franklin Rd. to it's intersection
with the Conrail Tracks, and the mark in the NW angle of the
intersection; 26 ft. W of the centerline of the road; 23.5 NE
of the NE rail; 10 ft. S of power pole; and about 0.2 ft above
the ground. A standard USC&GS BM tablet in a conc. post stamped
"S 245 1947" 851.809

DNR STA In Marion Co., NW 1/4 Sec. 33, T15N, R4E, About 5.7 Miles NE of
LI TT A12 Southport. From the interchange of Emerson Ave. and I-465 go
3/4 mile west on I-465 to the mark on the north side of the
highway; 3.9 ft. S. of right-of-way fence; 35.2 ft. SW of and
across the fence from the SW corner of a brick and conc. block
garage; and about flush with the ground. A standard DNR Div.
of Water control station tablet in a concrete post stamped "LI
TT A12" 802.597

MARION COUNTY
BEECH GROVE QUAD

MARK

ELEVATION
FEET
(NGVD 29)

DNR STA In Marion County, W. 1/2 Sec. 22, T14N, R4E., From the circle
PRG A5 at Indianapolis, thence travel about 9.7 miles Southerly to the
 intersection of Madison Ave. and County Line Road; thence East on
 County Line Road for about 1.9 miles to Emerson Avenue; thence
 about 0.5 miles North on Emerson to it's intersection with Todd
 Road and the mark. A standard Indiana Department of Natural
 Resources bronze tablet set in a 6" x 6" concrete monument about
 15 feet South of the center of Todd Road and about 7 feet East
 of the east edge of pavement of Emerson Ave. 815.165

MARION COUNTY
BRIDGEPORT QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM GC 1	In Marion County, NW 1/4 Sec. 14, T14N, R2E. About 1.55 miles east of Camby, 1.80 miles east along Camby Road from its intersection with State Road 67 in Camby to a 45 foot concrete bridge over Goose Creek, set in the top of the east end of the south conc. guardrail of the bridge, 13 feet south from the centerline of the road, 4.3 feet west from the east end of the south guardrail, 3.4 feet above the road, a chiseled triangle. 728.000
DNR TBM WR 200	In Marion County, W. 1/2 Sec. 12, T14N, R2E. About 2.65 miles northeast of Camby, 2 miles east along Camby Road from its intersection with State Road 67 in Camby, to a northeast-southwest T-road (Mooreville Road), thence 0.55 mile northeast along Mooreville Road to a gravel crossroad (Mills Road), thence 0.5 mile east along Mills Road to a 10 foot box culvert under the road, set in the top of the east end of the south concrete guardrail of the culvert, 9 feet south from the centerline of the road, 3.8 feet west from the east end of the guardrail, 2.5 feet above the road, a chiseled triangle. 717.898
DNR BM MAR 173	In Marion County, in the S. 1/2 Sec. 16, T15N, R2E. About 0.3 mile north of Bridgeport, 0.5 mile north along Bridgeport Road from its junction with U.S. 40 in Bridgeport to a 3-span concrete bridge over East Fork White Lick Creek, set in the top of the north end of the west sidewalk of the bridge, 15.0 feet west of the centerline of the road, 1.9 feet south of north end of bridge, 0.6 foot above the bridge floor, 0.8 foot east of east face of guardrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 173 1964". 754.612
DNR TBM EFWL 12	In Marion County, in the N. 1/2 Sec. 16, T15N, R2E. About 0.8 mile north of Bridgeport, 0.8 mile north along Bridgeport Road from its junction with U.S. 40 in Bridgeport to a 55 foot bridge over Salem Creek, set in the top of the south end of the east sidewalk of bridge, 16.0 feet east of centerline of road, 0.8 foot above the level of the road, 0.4 foot west of west face of guardrail, 0.2 foot north of south end of sidewalk, a chiseled square. 754.126
USGS TBM 83/LI	In Marion County, E. 1/2 Sec. 24, T14N, R2E. About 1.7 miles northeast of Landersdale, 2.0 miles generally northeast along Mann Road from the crossroad at Landersdale to a 40 foot concrete bridge over Swamp Creek, set in the top of the northwest concrete headwall, 160 feet northeast of the junction of Ralston Road and Mann Road, 23.5 feet southwest of the northeast end of the northwest headwall, 16.0 feet northwest of the centerline of Mann Road, 2.5 feet above the road, 0.5 foot southeast of the northwest edge of the headwall, a chiseled square. 676.038

MARION COUNTY
BRIDGEPORT QUAD

ELEVATION
FEET
(NGVD 29)

MARK

INDOT BM In Marion County, in the NW Sec. 21, T.15N, R.2 E. At Bridge-
MAR G3 port, at the U.S. Highway 40 bridge over East Fork White Lick
Creek, set in the top of the northwest concrete wingwall of
bridge, 32.5 feet north of center line of U.S. 40, 0.7 foot east
of west face of wingwall, 0.9 foot north of north face of guard-
rail about level with the roadway, a standard Indiana State
Highway Commission bronze benchmark tablet, stamped "MAR G 3".
750.829

MARION COUNTY
CARMEL QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 80	In Marion County, at Ravenswood, SE 1/4 Sec. 25 T.17N, R3E, at the intersection of Fitch Avenue and Stamm Avenue, in the north-east quarter of the junction, set in the top of a concrete post, 21.0 feet east from the centerline of Fitch Avenue, 16.0 feet north from the centerline of Stamm Avenue, level with the ground, a IFC&WRC benchmark tablet, stamped "MAR 80". 720.028
DNR TBM W 51	In Marion County, at Ravenswood, N. 1/2, Sec. 25, T.17N, R.3E., at the intersection of east 75th Street and Rosslyn Street, set in the north side of a 20 inch tree, 62.0 feet north from the centerline of E. 75th Street, 58.0 feet east from the centerline of Rosslyn Street, about 0.9 foot above ground, a railroad spike. 722.630
DNR BM MAR 82	In Marion County, at Ravenswood, NW 1/4, Sec. 30, T.17N, R. 4 E. 0.2 mile west along E 75th Street from its junction with Key-stone Avenue, set in the top of a concrete post, at residence of 2217 E. 75th Street, 29.5 feet northeast from the northwest corner of a Stucco building, 22.5 feet south from the centerline of E. 75th Street, level with the ground, a IFC&WRC benchmark tablet stamped "MAR 82" 729.765
DNR TBM W 52	In Marion County, at Ravenswood, NW 1/4, Sec. 30, T.17N, R.4E., 0.2 mile west along E. 75th Street from its junction with Key-stone Avenue, to the residence of 2230 E. 75th Street, set in the top of the concrete curbing, 20.0 feet north from the centerline of E. 75th Street, 2.0 feet north from the south end of the west concrete curbing, along driveway, 0.3 foot above ground, a chiseled triangle. 731.283
USED TBM 42	In Marion County, at Indianapolis, NW 1/4, Sec. 36, T.17N, R.3E. At the Louisville and Nashville Railroad Bridge over White River, set in the top of the southwest concrete wingwall of the bridge, 9.7 feet south from the north face of the south head-wall, 7.0 feet west from the west rail of tracks. 1.0 foot below the top of rails, 0.4 foot north from the south face of the southwest wingwall a chiseled square. 724.009
DNR STA TT A6	In Marion County, at Indianapolis, on Sec. Line between Sec. 31 and 36, T.17N., R4E, 0.05 mile north along Evanston Avenue, from its intersection with East 66th Street, to a small bridge over Bailey Creek, 11.0 feet west from the centerline of Evanston Avenue, 2.0 feet east from east face of northeast corner of the west concrete headwall of bridge, set in the roadway, 0.3 foot below the top of asphalt, a 1 inch steel road set in concrete. 723.053

MARION COUNTY
CARMEL QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR STA LEA B9	In Marion County, NE 1/4, Sec. 25, T.17N, R2E. About 1060' south along Georgetown Road (Coffman Road on quad) from its intersection with West 79th Street at the southwest corner of a Conrail crossing, a standard IDNR disk set in a concrete monument, 31.67 feet east from 4 inch cherry tree, 35.56 feet southerly from cut "X" in base bolt of railroad signal, 107.98 feet westerly from cut "X" in basebolt of railroad signal. 851.53
DNR STA TT A12	In Marion County, at Indianapolis, N 1/2 Sec. 25, T.17N, R.3E, Northeast from the intersection of Westfield Road and Barlum Drive. Mark is a 1 inch steel rod set in concrete 0.2 feet below ground 3.0 feet west of south end of wooden fence and on line with hedgerow to the east; 75.5 feet northeast from the intersection of Westfield Road and Barlum Drive. 763.431
DNR STA TT A13	In Marion County, at Indianapolis, NE 1/4 Sec. 24, T.17N, R3E. Travel west on 86th St. (old SR 100) from its intersection with Indiana Highway 431, 0.70 miles to station on left, chiseled cross in NE corner of exit drive on east side of North Central High School, 2.7 feet north of back of curb and 15.6 feet west of east end of curb, 24.1 south of 86th St. (old SR 100) centerline. 765.453
DNR STA CCA A1	In Marion County, at Indianapolis, NE 1/4 Sec. 18, T.17N, R3E. On the north side of west bound I-465, at the east end of the west bound I-465 bridge over Michigan Road (421) about 900 feet southeast of the intersection of Michigan Road with West 96th St., 2.32 feet northeast from cut "X" on north concrete wingwall on east side, 9.55 feet northwest of cut "X" top of 3rd guard rail post from end of bridge, a disc set in concrete. 896.457

MARION COUNTY
CARMEL QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR STA LEA B8	In Marion County, at New Augusta, SW 1/4 Sec. 30, T.17N, R.3E. At the northeast corner of this intersection of West 71st Street with the Conrail track, about 4000 feet west of Rodebaugh Road, 43.88 feet southwesterly from nail & B.C. in telephone pole, 9.3 feet north from north edge of West 71st Street, 20 feet east from east edge of rail of Conrail tracks, a standard disk set in concrete. 830.40
DNR STA CCA A4	In Marion County, S. 1/2 Sec. 28, T.17N, R.3E. About 4900' east along Westlane Road (West 73rd Street on quad from its in- tersection with Michigan Road, on the south side of Westlane. About 150' east of Harcourt Road entering from the north, a standard IDNR disk set in a concrete monument, 58.31 feet north- easterly from nail & B.C. in 8 inch twin elm, 87.45 feet south- easterly from four 6 inch willow trees, 62.78 feet northwesterly from nail & B.C. in power pole 3-262-A. 791.586
DNR STA CCA A3	In Marion County, SE 1/4 Sec. 29, T17N, R3E. At the inter- section of Michigan Road and Westlane Road, in the northeast corner of the intersection, 1.9 miles southeast of the intersec- tion of Michigan Road and West 86th Street, a standard IDNR disk set in a concrete monument, 8.48 feet west of nail & B.C. in telephone pole, 44.66 feet southerly from cut "X" on base bolt of shell sign, 9.60 feet northeasterly from nail & B.C. in light pole 220-260-A. 812.724
DNR STA CCA A2	In Marion County, W. 1/2 Sec. 20, T.17N, R.3E. About 2400 southeast along Michigan Road from its intersection with West 86th Street, on the east side of Michigan Road, a standard IDNR disk set in a concrete monument, 91.95 feet northeasterly from nail & B.C. in 6 inch elm, 150.15 feet east from nail and B.C. in power pole 46 /99-B, 20.64 feet southerly from nail & B.C. in telephone pole. 849.419

MARION COUNTY
CARMEL QUADRANGLE

MARK	ELEVATION FEET (NGVD 29)
DNR TBM WC 8 1989	In Marion County, Carmel Quadrangle, Southwest 1/4 of section 25, T. 17 N., R. 3 E., Located at the bend in the road where East 71st. St. and North Williams Creek Drive intersect. Set in the north side of a utility pole, 32.5 feet northeast from a street sign, 16 feet east of the centerline of N. Williams Creek Dr. 1.3 feet above the ground. A railroad spike. 715.786
DNR BM MAR 250 1989	In Marion County, Carmel Quadrangle, near the center of section 15, T. 17 N., R. 3 E., Located at the West 91st Street bridge over Williams Creek. Set in the top of the southwest concrete wingwall of the bridge, 18.5 feet south of the centerline of West 91st Street, 3.9 feet north of the south end of wingwall, level with the road, A standard Dept. of Natural Resources control station tablet, stamped "MAR 250 1989". 792.096
DNR BM MAR 251 1989	In Marion County, Carmel Quadrangle, Southeast 1/4 of section 15, T. 17 N., R. 3 E., located about 0.3 miles Southwest along Pine Drive from its intersection with West 91st Street. Set in the top of a 8.0 feet concrete culvert at the residence of 650 Pine Drive. 63.0 feet southwest of the residence mailbox, 11.4 feet northwest of the centerline of Pine Drive, Level with the road-way, A Department of Natural Resources control station tablet stamped, "MAR 251 1989". 809.760
DNR TBM WC 5 1989	In Marion County, Carmel Quadrangle, Section 15, T. 17 N., R. 3 E., Located near the West 86th street bridge over Williams Creek. Set in the west side of utility pole #295-204-B, 200 feet east of the bridge, 49.3 feet south of the centerline of West 86th Street, 1.0 foot above the ground, A railroad spike. 798.862
DNR TBM WC 6 1989	In Marion County, Carmel Quadrangle, Southwest 1/4 of section 23, T.17 N., R. 3 E., Located at the intersection of Spring Mill Road and Williams Drive. Set in the east side of a utility pole #358-235, in the south-east quadrant of the intersection, 26.5 feet south of the centerline of Williams Drive, 25.5 feet east of the centerline of Spring Mill Road, 1.1 feet above the ground, A railroad spike. 761.594

MARION COUNTY
CARMEL QUADRANGLE

MARK	ELEVATION FEET (NGVD 29)
INDOT BM MAR G132	In Marion County, Carmel Quadrangle, Northwest 1/4 of section 26, T. 17 N., R. 3 E., Located at the U.S. Highway 31 bridge over Williams Creek, Set in the top of the southwest concrete wingwall of the bridge. 37.0 feet west of the centerline of U.S. 31 , 1.0 foot west of the west concrete guardrail, 1.5 foot above the roadway, A Indiana State Highway Commission control station tablet stamped, "MAR G132". 754.790
INDOT BM HAM C44	In Hamilton County, Carmel Quadrangle, Southeast 1/4 section 10, T.17 N., R. 3 E., Located at the Interstate 465 bridge over Williams Creek. Set in the westbound lane bridge in the top of the northwest concrete head-wall, 13.8 feet north of the north edge of the roadway, 1.6 feet west of the east end of the headwall, 0.7 feet above the roadway, A Indiana State Highway Commission control station tablet stamped, "HAM C44". 809.083
DNR TBM WC 7 1989	In Marion County, Carmel Quadrangle, Northwest 1/4 of section 25, T. 17 N., R. 3 E., Located near the College Avenue bridge over Williams Creek. Set in the south side of utility pole #32-237, 140 feet south of the south end of bridge, 23.0 feet east of the centerline of College Avenue, 1.4 feet above the ground. A Railroad Spike. 737.695
DNR BM MAR 252 1989	In Marion County, Carmel Quadrangle, section 25, T. 17 N., R. 3 E., Located at the East 75th St. bridge over Williams Creek. Set in the top of the northeast concrete headwall of the bridge, 21.8 feet north of the centerline of East 75th Street, 0.5 feet south of the north face of the headwall, 0.9 feet above the roadway, A Department of Natural Resources control station tablet stamped, "MAR 252 1989". 733.727
DNR TBM PIVOT POINT 1 1989	In Marion County, Carmel Quadrangle, Northeast 1/4 section 25 T. 17 N., R. 3 E., Located at the intersection of East 75th Street and Ralston Avenue, in the southeast quadrant of the intersection, set in the southeast side of utility pole # 297-0239, 25.0 feet south of the centerline of East 75th Street, 23.5 feet east of the centerline of Ralston Avenue, 0.9 feet above the ground, A railroad spike. 723.405

MARION COUNTY
CARMEL QUADRANGLE

MARK	ELEVATION FEET (NGVD 29)
DNR TBM PIVOT POINT 4 1989	In Marion County, Carmel Quadrangle, Southeast 1/4 of section 15, T. 17 N., R. 3 E., Located at the intersection of West 91st Street and Coventry Road, In the southeast quadrant of the intersection. Set in the south side of utility pole 351-205A, 29.0 feet east of the centerline of Coventry Road, 20.0 feet south of the centerline of West 91st Street, 0.7 feet above ground level, A railroad spike. 824.280
DNR TBM PIVOT POINT 5 1989	In Marion County, Carmel Quadrangle, Northeast 1/4 of section 15, T. 17 N., R. 3 E., Located 0.15 miles west along Pine Drive from the intersection of Pine Drive and Spring Mill Rd., Set in the N.W. side of a fire hydrant, A flange bolt stamped "IDNR TBM". 826.703
DNR TBM PIVOT POINT 6 1989	In Marion County, Carmel Quadrangle, Northeast 1/4 of section 15, T.17 N., R.3 E. Located at the intersection of West 96th Street (Hamilton-Marion County Line Road) and Spring Mill Road, set in the southeast quadrant of the intersection, Set in the north side of a utility pole, 25.5 feet west of the centerline of Spring Mill Road, 18.0 feet south of the centerline of West 96th Street, 1.1 feet above the ground, A railroad spike. 827.539
DNR BM MAR 81	In Marion County, Carmel Quadrangle, NE 1/4 section 25 T. 17 N., R. 3 E., Located about 0.1 miles north along Rosslyn Street from the intersection of East 75th Street and Rosslyn Street, at the residence at 7583 Rosslyn Street, 70 feet north-northeast of the north-northeast corner of the residence, 26 feet south of the south edge of White River, 6.5 feet west of a fence corner post, 3.7 feet southwest of a 10 inch Ash tree, A Standard IFC&WRC control station tablet stamped "MAR 81". 717.895

MARION COUNTY
CARMEL QUADRANGLE

MARK

ELEVATION
FEET
(NGVD 29)

DNR TBM
TT A9
1970

In Marion County, Carmel Quadrangle, NE 1/4 section 35,
T. 17 N., R. 3 E., At the College Avenue bridge over
White River, about 200 feet south of the south end of
bridge, + 150 feet northwest of entrance drive to the
Edgewood Apartment complex, Set in the north side of a
concrete catch basin on the median between north and
south bound College Avenue, On the centerline of island
where the asphalt portion of island changes to grass, A
chiseled cross. 726.926

DNR TBM
TT A10
1970

In Marion County, Carmel Quadrangle, NE 1/4 section 35,
T. 17 N., R. 3 E., At the College Avenue bridge over
White River, Set in the centerline of the first traffic
island north of the intersection of College Avenue and
70th Street, + 300 feet north of the north end of the
bridge over White River, Set in the south end of the
pavement of the island, A chiseled cross. 726.201

MARION COUNTY
CLERMONT QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 112	In Marion County, at Indianapolis, NW 1/4 Sec. 6, T.15N., R.3E. At the Lynhurst Street bridge over Eagle Creek, set in the north end of the east sidewalk, 25 feet east of the centerline of Lynhurst Street, 15 feet south of the north end of the east sidewalk, 0.3 foot above road, on east edge of east sidewalk, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 112 1958." 730.036
DNR TBM A	In Marion County, at Indianapolis, NW 1/4 Sec. 6, T.15N., R.3E., near the northeast end of the Lynhurst Street Bridge over Eagle Creek, at the Allisonville Pumping Station. About 40 feet east of the low concrete of the east side of the bridge, 21 feet southwest of Power Pole #57-496, at the northwest corner of the concrete base, 0.5 foot south of north edge of concrete base, the screw end of the north bolt of the northwest post of the pumping station. 718.747
DNR BM MAR 12 RESET 1960	In Marion County, at Speedway, Indianapolis, SW 1/4, Sec. 36, T.16N., R.2E. At the Baltimore and Ohio Railroad bridge over Eagle Creek, 0.8 mile west of the intersection of 16th Street and Lynhurst Drive in Speedway, set in the top of the east abut- ment, 7.6 of the north rail of the track, 6 feet below the tracks, 1.1 feet south of the north edge and 1.1 feet west of the east edge of the east abutment (or bridge seat), a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 12 RESET 1960". 730.215
DNR TBM 1	In Marion County, at Speedway, Indianapolis, in SW 1/4, Sec. 36, T.16N., R.2E. At the Baltimore and Ohio Railroad bridge over Eagle Creek, 0.8 mile west of the intersection of 16th Street and Lynhurst Drive in Speedway, the top of the head of a 1/2 inch bolt a the northeast end of the girder base at the north- east corner of the bridge, 6.5 feet north of the north rail of the track, 4.7 feet below the tracks, 2 feet west of the east edge of the east abutment (or bridge seat) a 1/2 inch bolt head. 731.133
DNR BM MAR 8 RESET 1960	In Marion County, in SW 1/4, Sec. 22, T.16N., R.2E., at the Dandy Trail Bridge over Eagle Creek on the northwest end of the southwest bridge seat. 0.35' S.E. of N.W. face of bridge seat 0.35' S.W. of N.E. face of bridge seat 3.5' below the roadway 19' N.W. of centerline of Dandy Trail. A standard IFC&WRC disk stamped "MAR 8 RESET 1960". 757.859

MARION COUNTY
CLERMONT QUAD

MARK	ELEVATION FEET (NGVD 29)
INDOT BM MAR 0102	In Marion County, NW 1/4 Sec. 22, T.16N., R.2E. About 0.95 miles northeast of Clermont, At the interstate 74 twin bridges over Eagle Creek, set in the top at the northwest end of the northeast sidewalk of the northeast (upstream) bridge of the twin bridges over the Creek, 16.5 feet northeast of the centerline of the road, 7.5 feet southeast of the northwest end of the northeast sidewalk of the bridge, 0.9 foot above the roadway, a standard ISHC benchmark tablet, stamped "MAR 0102". 768.947
DNR TBM EFWL 13	In Marion County, in the S. 1/2 Sec. 9, T.15N., R.2E. About 0.8 mile south of Tremont, 0.9 mile south along Bridgeport Road from its junction with U.S. 36 in Tremont to 30 foot concrete bridge over Davon Creek, set in the top of the north end of the west concrete guardrail of bridge, 15.5 feet west of centerline road, 1.0 foot above the level of the road, 0.8 foot south of north end of guardrail, at the top peak of guardrail, a chiseled square. 762.095
NGS BM B 77	In Marion County, in the N. 1/2 Sec. 9, T.15N., R.2E. About 0.3 mile southwest of Tremont, 0.3 mile south along Bridgeport Road in Tremont to the New York Central Railroad overpass, set in the top of the south end of the northeast wingwall of overpass, 6.5 feet north of north rail of tracks, 1.1 feet east of west face of wingwall, 1.7 feet below the level of the tracks, a standard USC&GS bronze benchmark tablet, stamped "B 77 1946". 794.788
DNR TBM EFWL 15	In Marion County, in the SW 1/4 Sec. 33, T.16N., R.2E., about 1.1 miles north-northwest of Tremont, 0.5 mile west along U.S. 36 from its junction with Bridgeport Road in Tremont to a north-south crossroad (County Line Road), thence 1.0 mile north to an east-west crossroad (10th Street), thence 0.1 mile east to a 10 foot concrete bridge over Westwood Branch, set in the top of the northwest wingwall of bridge, 15.5 feet north of centerline of road, 0.6 foot north of north face of concrete guardrail, 0.4 foot southwest of northeast face of wingwall, about level with the roadway, a chiseled triangle. 801.340
DNR BM MAR 178	In Marion County, in the NW 1/4 Sec. 33, T.16N., R.2E., about 1.5 miles south of Clermont, 2.0 miles south along County Line Road from its junction with U.S. 136 in Clermont to a 30 foot concrete bridge over East Fork White Lick Creek, set in the top of the north end of the east concrete curbing of bridge, 13.0 feet east of centerline of road, 0.9 foot above the level of the roadway, 2.1 feet south of north end of curbing, 0.4 foot west of east face of curbing, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 178 1964". 805.638

MARION COUNTY
CLERMONT QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 176	In Marion County, in NE 1/4 Sec. 4, T.15N., R.2E. About 0.8 mile northeast of Tremont, 0.5 mile east along U.S. 36 from its junction with Bridgeport Road in Tremont to a T-road north, thence 0.9 mile north to a 40 foot concrete arch bridge over East Fork White Lick Creek set in the top of the northwest wingwall of bridge, 16.5 feet west of centerline of road, 0.7 foot north of south face of wingwall, 0.9 foot west of west face of concrete guardrail, about level with the roadway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 176 1964". 781.736
DNR BM MAR 7 RESET	In Marion County, at Indianapolis, SW 1/4 Sec. 6, T.16N., R.3E. At the West 56th Street bridge over Little Eagle Creek, 0.7 mile east of the junction of West 56th Street and U.S. 52, set in the top of the north concrete guardrail of the bridge, 22.8 feet west of the east end of the north guardrail, 16 feet north of the centerline of the road, 3.4 feet above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 7 RESET 1962". 795.305
DNR BM MAR 10	In Marion County, at Indianapolis, NW 1/4 Sec. 26, T.16N., R.2E. At the abandoned Conrail Railroad Bridge over Eagle Creek, 2.0 miles southeast from Clermont about 400 feet south of U.S. Highway 136, on the southeast wingwall, 1.5 feet east of west face of bridge seat, 2.6 feet south of base of southeast corner of truss, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 10". 742.675
DNR STA LEA B7 RESET 1985	In Marion County, at Indianapolis, NE 1/4 Sec. 12, T.16N., R.2E, At the intersection of West 56th Street and Moller Road, 12.96 feet northwesterly of concrete R/W Monument, 46.2 feet southwesterly of 21 inch Tulip Tree, 43.6 feet easterly of Moller Road centerline a standard DNR Division of Water control station tablet in a concrete post stamped "LEA B 7 RESET 1985". 808.19
DNR BM MAR 170	In Marion County, at Indianapolis, at the junction of West 52nd. Street and U.S. 52, set in the top of the northeast end of the southeast headwall of an 18 inch pipe culvert under the intersection, 50.5 feet northeast of the centerline of the road, 36 feet south of the centerline of West 52nd Street, 1.25 feet southwest of the northeast face of the southeast headwall, 0.2 foot below the centerline of West 52nd Street, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 170 1962". 799.708

MARION COUNTY
CUMBERLAND QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM BC 35	In Marion County, S. 1/2 Sec. 10, T.15N., R.5E. About 1.45 miles south of Cumberland, 1.45 miles south along the Hancock-Marion County Line Road from its junction with U.S. Highway 40 at the east edge of Cumberland to a crossroad (Prospect Street), thence 0.47 mile west along Prospect Street to the Prospect Street bridge over Buck Creek, at the northeast corner of the bridge, set in the top of the east end of the north guardrail base, 17 feet north of the centerline of the road, 0.8 feet above the roadway, 0.3 foot south of the north edge of the bridge, 0.3 foot west of the east end of the bridge, a chiseled square. 820.129
DNR TBM BC 34	In Marion County, NW 1/4 Sec. 15, T.15N., R.5E. About 1.9 miles southwest of Cumberland, 1.45 miles south along the Hancock-Marion County Line Road from its junction with U.S. Highway 40 at the east edge of Cumberland to a crossroad (Prospect Street), thence 1.0 mile west along Prospect Street to a crossroad (German Church Road), thence 0.34 mile south along German Church Road to House Number 1509, set in the west side of a power pole Number 59 and 13-581E, 85 feet north of the centerline of the driveway to the above residence or R.R. 10, Box 412, 11.5 feet east of the centerline of the road, 5 feet west of a T-fence corner post and fence line, 0.5 feet above the roadway, a rail-road spike driven through an aluminum tag, stamped "BC 34 1959". 835.275
NGS BM D 238	In Marion County, SE 1/4 Sec. 3, T.15N., R.4E. About 0.4 mile southeast of Cumberland, 0.32 mile south along the Marion-Hancock County Line Road from its junction with U.S. Highway 40 (at the east city limits of Cumberland) to a concrete arch bridge over Buck Creek, set in the top at the south end of the west guardrail of the bridge, 9 feet west of the centerline of the County Line Road, 1.5 feet above the bridge floor, set in the top at the northeast corner of the southwest post of the west guardrail, a stamped USC&GS benchmark tablet, stamped "D 238 1947". 828.496
NGS BM B 238	In Marion County, NE Sec. 3, T.15N., R.5E. About 0.42 mile north of Cumberland, 0.25 mile west along U.S. Highway 40 from its junction with the Hancock-Marion County Line and Road to a T-road north (Cumberland Road), thence 0.42 mile north along Cumberland Road to a crossroad (East 10th Street), at the intersection, in the southwest quarter, set in the top of a concrete post projecting 0.5 foot above the ground, 30 feet west of the centerline of Cumberland Road, 23 feet south of the centerline of East 10th Street, about level with the road, a standard USC & GS benchmark tablet, stamped "B238 1947". 856.147

MARION COUNTY
FISHERS QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM F 2	In Marion County, NW 1/4 Sec. 36, T.17N., R.4E., In Indianapolis, at the intersection of Fall Creek Road, and Hague Road, set in the top near the center of a 5 foot concrete headwall of a 1.0 foot pipe culvert, 4.0 feet north from the centerline of Fall Creek Road, 17.5 feet east from the centerline of Hague Road, 0.1 foot below roadway, a chiseled square. 840.559
DNR BM MAR 43	In Marion County, NE 1/4 Sec. 36, T.17N., R.4E., In Indianapolis at the intersection of Fall Creek Road, at North Lantern Road, set in the top of the southeast concrete wingwall of a 10 foot concrete bridge over an unnamed ditch, 217.0 ft. west from the centerline of North Lantern Road, 13.3 feet south from the centerline of Fall Creek Road, 0.5 foot southeast of east end of south concrete guardrail, 0.2 foot below the roadway, a standard Indiana Flood Control and Water Resources Commission benchmark tablet, stamped, "MAR 43". 769.422
NGS BM W 236	In Marion County, NE 1/4 Sec. 31, T.17N., R.5E., In Indianapolis, 0.6 mile north along Lee Road, from its intersection with east 63rd Street, (Fort Benjamin Harrison) set in the top of the northwest concrete wingwall of a 10 foot concrete bridge over a ditch, 81.0 feet north from the centerline of Trilobi Drive, 14.0 feet west from the centerline of Lee Road, 0.3 foot below roadway, a standard USC&GS benchmark tablet, stamped "W 236 1947" 760.090
USGS RM 1	In Marion County, NE 1/4 Sec. 25, T.17N., R.4E., 225 feet east along North Lantern Road, from its intersection with North Sargent Road to a one-span concrete deck bridge over Mud Creek, set in the top of the southeast concrete wall of the bridge, 10.0 feet south from the centerline of road, 1.3 feet above roadway, 0.6 foot west from the east face of wingwall, a standard USGS gaging station disk, not stamped. 766.047
USGS RM 3	In Marion County, NE 1/4 Sec. 25, T.17N., R.4E., 225 feet east along North Lantern Road from its intersection with North Sargent Road, to a one-span concrete deck bridge over Mud Creek, set in the top of the southwest concrete wingwall of the bridge, 12.0 feet south from the centerline of the road, 1.1 feet above roadway, 1.0 foot south from north face of wingwall, the round head of a bolt. 765.997

MARION COUNTY
FISHERS QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM B	In Marion County, NE 1/4 Sec. 36, T.17N., R.4E., 0.45 mile generally southwest along North Sargent Road from its intersection with east 75th Street, set in the west side of a 26" hackberry tree, 17.0 feet east from the centerline of north Sargent Road, 26.0 feet north from the centerline of driveway, (7033 N. Sargent Road) 18.0 feet southwest from an end fence post, 0.5 foot below the roadway, about 0.2 foot above ground, a railroad spike driven through a brass tag (the stamping is no longer readable). 765.808
INDOT BM MAR G 10	In Marion County, NW 1/4 Sec. 20, T.17N., R.4E., In Indianapolis, at the Allisonville Road 4-span steel truss bridge over White River, set in the top of the northwest concrete bridge seat, 19.0 feet northeast from the centerline of Allisonville Road, 6.0 feet below the roadway, 0.5 foot southwest of the northeast edge of the northwest bridge seat, a standard ISHC benchmark tablet, stamped "MAR G 10". 733.289
NGS BM E 237	In Marion County, NW 1/4 Sec. 15 T.17N., R4E., In Indianapolis, at the intersection of Allisonville Road and East 96th Street, set in the top of a concrete post, set in the SE quarter of the junction, 65.0 feet south from the centerline of East 96th Street, 44.5 southeast from the centerline of Allisonville Road, 8.0 feet southwest of a right-of-way marker, 2.5 feet below the roadway, a standard USC & GS benchmark tablet, stamped "E 237 1947" 767.774
DNR STA TT A1	In Marion County, NW 1/4 Sec. 33, T.17N., R4E., In Indianapolis. Mark is 600 feet east of Allisonville Road and East 71st Street intersection. Mark is a 1 inch steel rod located under asphalt driveway at south edge of 71st Street and in line with west edge of said asphalt driveway leading to house (#4821), 54.2 feet, N 80` W from 12 inch tree; 6.3 feet, N 90` W from centerline of drive; 10.6 feet, N 0` E from road centerline. 783.909
DNR STA TT A2	In Marion County, on sec. line between Sec. 29, 32, T.17N., R.4E., at Indianapolis, at the intersection of E. 71st Street and Cranbrook Drive, set on the north edge of E.71st Street and the centerline of Cranbrook Drive, at the entrance to Slyvan Ridge Sub Division. 37.1 feet southeast from southeast corner of the west red brick pillar post, 43.1 feet southwest of the southwest corner of the east red brick pillar post, 10.2 feet north from the centerline of E. 71st Street, a one inch steel rod driven flush with the roadway. 753.081

MARION COUNTY
FISHERS QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR STA TT A4	In Marion County, NW 1/4 Sec. 31, T.17N., R.4E., In Indianapolis at the intersection of E. 71st Street and Tacoma Street, in the southwest quarter of the intersection, 42.8 feet west from a fire hydrant, 25.8 feet south from the centerline of Tacoma Street, 3.0 feet north from a end fence post. 1.0 foot below ground, a one inch steel rod set in the top of a concrete post. 731.450
DNR STA TT B3	In Marion County, at Indianapolis, N 1/2 Sec. 20, T.17N., R.4E., at the intersection of E. 82nd Street and Dean Road, in the southwest quarter of the intersection, 46.4 feet south from the centerline of E. 82nd Street, 19.7 feet west from the centerline of Dean Road, 11.5 feet west from a steel grate in Dean Road, 0.4 foot below ground, a one inch diameter steel rod driven in ground. 734.041
DNR BM MAR 1-8783	In Marion County, Fishers Quad, N. 1/2 Sec. 36 T.17N., R.4E., approximately 0.5 miles east on Fall Creek Road from its junction with Hague Road to concrete bridge over Mud Creek. A standard IDNR BM tablet set in the southwest abutment of the bridge; 22.8 ft. south of centerline of Fall Creek Road and 0.5 ft. east of the west end of the abutment. The tablet is stamped "MAR 1-8783." 759.61
INDOT BM MARG 357	In Marion County, Fishers Quad, N. 1/2, Sec. 36, T.17N., R.4E., approx. 0.5 miles east on Fall Creek Rd. from its junction with Hague Rd. to a concrete bridge over Mud Creek. Set in the top of the northeast abutment of the bridge; 22.2 ft. north of centerline of Fall Creek Rd.; 1.7 ft. west of the east end of the abutment. A standard Indiana State Highway Commission BM tablet stamped "MARG 357". 764.14

MARION COUNTY
FISHERS QUAD

MARK

ELEVATION
FEET
(NGVD 29)

DNR STA
TT A15

In Hamilton County, Fishers Quad, SE/ Sec. 8, T.17N
R.4E, on the Hamilton-Marion County line road (E. 96th
Street) 0.93 mile east along E. 96th Street from its
intersection with State Road 431, to the concrete
bridge over Carmel Creek. 36.7 feet northeast from 2
twin 20 inch trees, 12.5 feet north from centerline of
road, 2.0 feet south from the west end of the north
concrete headwall of bridge, a one inch diameter steel
rod, set 1.0 foot below ground. 737.807

DNR STA
A17

In Hamilton County, Fishers Quad, SE/ Sec. 9, T.17N, TT
R.4E, on the Marion-Hamilton County line road (E. 96th
Street) 0.1 mile east along E. 96th Street from its
intersection with North River Road, 126.0 feet west
from a circular Bell Telephone underground cable box,
(most western box of 2 boxes) 525 feet east from the
centerline of North River Road, 5.9 feet north from the
centerline of Dirt Road, (E. 96th Street), a one inch
steel rod set in concrete, 1 foot below ground. 733.308

MARION COUNTY
FISHERS QUADRANGLE

MARK	ELEVATION FEET (NGVD 29)
IDNR TBM HIMUSA 11 1989	Marion County, Fishers Quad, NW/ Sec. 25, T.17N, R.4E: Located near the intersection of North Hague Road and East 75th Street. Set in the southwest side of utility pole #60-249-B, northeast quadrant of the intersection, 32.0 feet north of East 75th Street centerline, 55.0 feet east of North Hague Road centerline, 1.0 foot above ground level; a railroad spike driven through an aluminum tag, stamped "HIMUSA 11 1989." 834.490
IDNR TBM HIMUSA 12 1989	Marion County, Fishers Quad, near the N. E. corner of sec 18, T.17N,R.5E: Located near the intersection of East 96th Street and Lantern Road (Hamilton-Marion County Line). Set in the northwest side of utility pole #2181-B, 93.0 feet south of East 96th Street centerline, 25.0 feet east of Lantern Road centerline, 1.2 feet above ground level; a railroad spike driven through an aluminum tag, stamped "HIMUSA 12 1989" 821.773
SECTION CORNER MONUMENT #3	Marion County, Fishers Quad, Section Corners 12-7-13- 18, T.17N, R.4 and 5E: A chrome plated rod in a steel box in the center of the road. 821.052
SECTION CORNER MONUMENT #4	Marion County, Fishers Quad, Section Corners 12-7-13- 18, T.17N, R.4 and 5E: A section corner monument, 76.0 feet south of monument #3. 821.048
IDNR BM MAR 272 1989	Marion County, Fishers Quad, SW/ Sec. 19, T.17N, R.5E: Located at the East 82nd Street Bridge over Mud Creek. Set in the north concrete wingwall of the bridge, 19.5 feet northeast of East 82nd Street centerline, 2.3 feet northeast of the northeast face of the concrete guard- rail, level with road; an IDNR control station tablet, stamped "MAR 272 1989." 774.446
IDNR BM MAR 273 1989	Marion County, Fishers Quad, N/ Sec. 19, T.17N, R.5E: Located at the East 86th Street Bridge over Mud Creek. Set in the south end of the east concrete bridge seat of the bridge, 18.0 feet south of East 86th Street centerline, 2.4 feet below the sidewalk, 0.3 feet north of the south face of the bridge seat; an IDNR control station tablet, stamped "MAR 273 1989." 778.318

MARION COUNTY
FISHERS QUADRANGLE

MARK	ELEVATION FEET (NGVD 29)
IDNR BM MAR 274 1989	Marion County, Fishers Quad, N/ Sec. 18, T.17N, R.5E: Located at the East 96th Street Bridge over Mud Creek (Hamilton-Marion County Line). Set in the south end of the east concrete pier, 19.0 feet south of East 96th Street centerline, 35.0 feet west of the east end of the bridge, 1.8 feet below road; an IDNR control station tablet, stamped "MAR 274 1989." 783.116
USCOE STA FALL	Marion County, Fishers Quad, SE/ Sec. 30, T.17N, R.5E: Located at the East 71st Street Bridge over Fall Creek (Fort Harrison Military Reservation). Set in the north concrete sidewalk of the bridge, 94.5 feet east of the west end of the bridge, 16.5 feet north of East 171st Street centerline, level with sidewalk; an Army Corps of Engineers control station tablet stamped "STA FALL" 786.693
IDNR TBM HIMUSA 1 1989	Marion County, Fishers Quad, SW/ Sec. 13, T.17N, R.4E: Located near the intersection of North Hague Road and East 86th Street. Set in the northwest side of utility pole #IPL 126-219-A, northeast quadrant of the inter- section, 89.0 feet east of the centerline of North Hague Road, 62.0 feet north of East 86th Street center- line, 1.2 feet above ground level; a railroad spike driven through an aluminum tag, stamped "HIMUSA 1 1989." 829.011
IDNR TBM HIMUSA 2 1989	Marion County, Fishers Quad, SW/ Section 13, T.17N, R.4E: Located near the intersection of East 86th Street and North Fawn Meadow Drive, 0.55 miles east along East 86th Street from its intersection with North Hague Road. Set in the south side of utility pole #IPL 7220-A, 32.0 feet north of East 86th Street centerline, 29.0 feet east of the extended centerline of North Fawn Meadow Drive, 1.0 feet above ground level; a railroad spike driven through an aluminum tag, stamped "HIMUSA 2 1989." 837.619

MARION COUNTY
FISHERS QUADRANGLE

MARK	ELEVATION FEET (NGVD 29)
IDNR TBM HIMUSA 3 1989	Marion County, Fishers Quad, SW/ Sec. 24, T.17N, R.4E: Located near the intersection of North Hague Road and East 82nd Street. Set in the north side of utility pole #54-00249-A, southeast quadrant of the intersec- tion, 29.0 feet south of East 82nd Street centerline, 103.0 feet east of North Hague Road centerline, 1.0 feet above ground level; a railroad spike driven through an aluminum tag, stamped "HIMUSA 3 1989." 838.039
IDNR TBM HIMUSA 4 1989	Marion County, Fishers Quad, SE/ Sec. 24, T.17N, R.4E: Located near the intersection of East 82nd Street and North Castle Lake Road, 0.5 miles east of the in- tersection of East 82nd Street and North Hague Road. Set in the north side of utility pole #55-250-A, 24.0 feet south of East 82nd Street centerline, 94.0 feet west of North Castle Lake Road centerline, 1.3 feet above ground level; a railroad spike driven through an aluminum tag, stamped "HIMUSA 4 1989." 839.430

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 38	In Marion County, at Indianapolis, NE 1/4 Sec. 18, T.16N., R.4E., on the Fall Creek Station water intake structure of the Indianapolis Water Company, about 300 feet southwest of the intersection of Keystone Avenue and Fall Creek Parkway, 200 feet downstream from the Keystone Avenue Bridge, 30 feet southwest of the northeast side of the wire fence enclosure around the intake, 2 feet southeast of the 3 inch pipe guardrail, level with top of the metal screen in the intake, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 38". 726.399
DNR BM MAR 40	In Marion County, at Indianapolis, SW 1/4 Sec. 9, T.16N., R.4E., 300 feet north of the intersection of Millersville Road and Sherman Drive, at the intersection of Millersville Road and 46th Street, on a bridge, on the east handrail, 3 feet south of the north end of the handrail, 3.5 feet above the roadway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 40". 743.099
DNR BM MAR 42 RESET	In Marion County, at Indianapolis, SE 1/4 Sec. 35, T.17N., R.4E. About 0.5 mile east along Fall Creek Boulevard from it's junction with State Road 100 to the new 62nd Street bridge over Fall Creek (leading into Ft. Benjamin Harrison), set in the top at the northwest end of the northeast concrete guardrail base, 16 feet northeast of the centerline of the bridge, 1.0 foot southeast of the northwest end of the northeast concrete guardrail base, 0.8 foot above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 42 RESET 1961". 761.366
DNR BM MAR 129	In Marion County, at Indianapolis, NW 1/4 Sec. 9, T.15N., R4E., at the Pennsylvania Railroad bridge over South Sherman Drive between East Washington Street and Pleasant Run, in the northeast quarter of the crossing, set in the top of a 5.0 foot by 3.0 foot concrete base of an abandoned railroad signal, 252 feet east of the east end of the Pennsylvania railroad bridge, 34.0 feet north of the north rail of the west bound track, 0.7 foot above the ground, about level with the top of the rail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 129 1959". 776.462
DNR BM MAR 127	In Marion County, at Indianapolis, NW 1/4 Sec. 9, T.15N., R.4E., at the South Sherman Drive bridge over Pleasant Run, set in the northeast corner of the bridge, 30.0 feet east of the center line of South Sherman Drive, 26.5 feet south of the north end of the bridge, 0.9 foot above the level of the roadway, a standard Indiana Flood Control and Water Resources bronze benchmark tablet, stamped "MAR 127 1959". 761.552

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM PR 1	In Marion County, at Indianapolis, NW 1/4 Sec. 9, T.15N., R.4E., at the South Sherman Drive bridge over Pleasant Run, set in the northeast corner of the bridge, 30.0 feet east of the centerline of South Sherman Drive. 4.7 feet above the roadway, 0.3 foot south of the north end of the north guard rail post of the east handrail of the bridge, a chiseled cross. 764.796
USGS RM 3	In Marion County, at Indianapolis, NW 1/4 Sec. 9, T.15N., R.4E. At the Brookville Road bridge over Pleasant Run, set in the top of a concrete post, 56.0 feet south of the centerline of Brookville Road. 29.7 feet east of the centerline of East Pleasant Run Parkway North Drive, 5.4 feet due east of the first street light pole south of Brookville Road on the east side of East Pleasant Run Parkway North Drive, about 0.5 foot above the level of the road, and about level with the ground, a standard USGS bronze reference tablet, not stamped. 766.864
USGS RM 2	In Marion County, at Indianapolis, NW 1/4 Sec. 9, T.15N., R.4E., at the Brookville Road bridge over Pleasant Run, set in the top of the west headwall at the SW corner of the bridge, 25.0 feet S. of the centerline of the bridge, 3.5 feet below the top of the iron handrail, 1.7 ft. E. of the west end of the bridge, 0.8 foot west of the east face of the west headwall, about level with the roadway, a standard USGS bronze reference tablet, not stamped. 767.527
USGS RM 1	In Marion County, at Indianapolis, NW 1/4 Sec. 9, T.15N., R.4E. At the Brookville Road bridge over Pleasant Run, set in the top of the east headwall at the northeast corner of the bridge, 25.0 feet north of the centerline of the bridge, 3.5 feet below the top of the iron handrail, 0.6 foot east of the west face of the east headwall of the bridge, about level with the roadway, a standard USGS bronze reference tablet, not stamped. 767.548
DNR BM MAR 128	In Marion County, at Indianapolis, NW 1/4 Sec. 9, T.15N., R.4E. At the Conrail bridge over Pleasant Run and E. Pleasant Run Parkway S. Drive, set in the top of a conc. guardwall on the E. side of Pleasant Run and on the S. side of the RR, 160 ft. S. of the S. side of the RR bridge over Pleasant Run, 17.3 ft. W. of the centerline of E. Pleasant Run Parkway S. Drive, (3.1 ft. below the top of the handrail), 1.0 ft. S. of the S. end of an iron handrail in the top of the conc. guardwall, 1.0 ft. above the road level of E. Pleasant Run Parkway S. Drive. A standard IFC&WRC bronze BM tablet, stamped "MAR 128 1959". 762.025

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM PR 2	In Marion County, at Indianapolis, N. 1/2 Sec. 9, T.15N., R.4E. At the junction of S. Linwood Avenue and E. Pleasant Run Parkway North Drive, set in the top of the west end of a sewer drain headwall, 19.0 feet south of the centerline of East Pleasant Run Parkway North Drive, 8.0 feet west of the extended centerline of Linwood Avenue, 1.0 foot east of the west end of the headwall, 0.4 foot above the level of East Pleasant Run Parkway, a chis- eled triangle. 768.017
NGS BM Y 242	In Marion County, at Indianapolis, SE 1/4 Sec. 4, T.15N., R.4E. About 3.65 miles east along U.S. Highway 40 from the Marion County Courthouse, in the 5000 block on East Washington Street, set in the top of the west end of the south concrete railing of a 90 foot concrete arch bridge over Pleasant Run, 53.0 feet east of the east curb of Pleasant Run Parkway, 5.9 feet south of the south curb of the street, about 3 feet above the level of the sidewalk, a standard USC&GS benchmark tablet, stamped "Y242 1947". 782.551
DNR BM MAR 130	In Marion County, at Indianapolis, SW 1/4 Sec. 3, T. 15N., R.4E. At the Emerson Avenue bridge over Pleasant Run, at the northeast corner of the bridge, set in the top of the north end of the east handrail, 17.5 feet east of the center line of the bridge, 3.1 feet above the top of the walkway, 1.3 feet south of the north end of the east handrail, a standard Indiana Flood Control and Water Resources bronze benchmark tablet, stamped "MAR 130 1959". 784.027
DNR BM MAR 131	In Marion County, at Indianapolis, W. 1/2 Sec. 3, T. 15N., R.4E. At the East Michigan Street bridge over Pleasant Run, set in the top of the east bridge seat on the south side of the south hand- rail at the southeast corner of the bridge, 65.0 feet west of the center line of East Pleasant Run Parkway South Drive, 27.5 feet south of the center line of East Michigan Street, 3.0 feet below the top of the south handrail, 0.9 foot west of the first joint west of the east end of the south handrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR.131 1959". 783.313
NGS BM Z 242	In Marion County, At Indianapolis, S. 1/2 Sec. 3, T. 15N., R.4E. About 4.2 miles east along U.S. Highway 40 from the Marion County Courthouse, at the junction of U.S. Highway 40 (East Washington Street) and Ritter Streets, set vertically in the north face of the northeast corner of Public School Number 57 building, 1.0 foot west of the corner, 2.5 feet above the ground, a standard USC&GS benchmark tablet, stamped "Z 242 1947". 818.102

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 132	In Marion County, at Indianapolis, N. 1/2 Sec. 3, T. 15N., R.4E. At the North Ritter Avenue bridge over Pleasant Run, set in the top of the east handrail at the southeast corner of the bridge, 26.3 feet east of the center line of the bridge, 3.8 feet above the walkway, 1.9 feet north of the south end of the east hand- rail, a standard Indiana Flood Control and Water Resources bronze benchmark tablet, stamped "MAR 132 1959". 798.486
DNR BM MAR 133	In Marion County, at Indianapolis, NE 1/4 Sec. 3, T. 15N., R. 4E. At the Pleasant Run Parkway bridge over Pleasant Run, set in the top of the east bridge seat on the north side of the north handrail at the northeast corner of the bridge, 28.5 feet north of the center line of the bridge, 7.6 feet west of the east end of the north handrail of the bridge, 3.0 feet below the top of the north handrail, about level with the walkway, a stan- dard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 133 1959". 790.263
USGS RM 1	In Marion County, at Indianapolis, E. 1/2 Sec. 3, T. 15N., R. 4E. At the North Arlington Avenue bridge over Pleasant Run, set in the top of the west handrail at the northwest corner of the bridge, 28.7 feet west of the center line of the bridge, 23.1 feet south of the north end of the west handrail, 2.9 feet above the top of the west walkway, a standard USGS bronze refer- ence mark tablet, not stamped. 798.868
USGS RM 2	In Marion County, at Indianapolis, W. 1/2 Sec. 2, T. 15N., R. 4E. At the North Arlington Avenue bridge over Pleasant Run, set in the top of the east handrail at the southeast corner of the bridge, 28.4 feet east of the center line of the bridge, 23.1 feet north of the south end of the east handrail, 2.9 feet above the top of the east walkway, a standard USGS bronze refer- ence mark tablet, not stamped. 800.70
NGS BM Z 245	In Marion County, at Indianapolis, NW 1/4 Sec. 17, T. 15N., R. 4E. At the Conrail railroad overpass at Prospect Avenue and Pleasant Run Parkway, set at the northwest end of the southwest retaining wall at the southeast end of the bridge, 8 rails northwest of mile post 107.5, 8 feet southwest of the southwest rail, 1.0 foot below the track, a standard USC&GS benchmark tablet, stamped "Z 245 1947". 761.960

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM PR 14	In Marion County, at Indianapolis, SW 1/4 Sec. 8, T. 15N., R. 4E., at the Citizens Gas and Coke Company, at the Railroad Bridge upstream about 400 feet from Prospect Ave., set in the top of the northwest end of the northwest wingwall guardrail support, 11.3 feet north of the north rail of the track, 2 feet southeast of the northwest end of the northwest wingwall, 1.0 foot below the track, a chiseled triangle. 743.858
DNR TBM PR 13	In Marion County, at Indianapolis, SW 1/4 Sec. 8, T. 15N., R. 4E. At the Citizens Gas and Coke Company, at the railroad spur bridge upstream about 750 feet from Prospect Avenue, set in the top of the levee wall adjoining the northeast wingwall of the spur railroad bridge, 8.3 feet north of the north rail of the track, 4.5 feet below the track, 0.9 foot northeast of the northeast end of the northeast bridge wingwall, a chiseled triangle. 743.898
DNR BM MAR 141	In Marion County, at Indianapolis, SE 1/4 Sec. 8, T. 15N., R. 4E. At the old US Hwy. 421 (Southeastern Avenue or Michigan Road) bridge over Pleasant Run, about 177 feet northwest of the Conrail railroad overpass, set in the top at the southeast corner of the southwest guardrail of the 140 foot concrete bridge, 17 feet southwest of the center line of the road, 3.2 feet above the road, 1.6 feet northwest of the southeast end of the southwest concrete guardrail, 1.5 feet southwest of the northeast edge of the south wingwall, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 141 1960". 759.733
DNR TBM PR 15	In Marion County, at Indianapolis, NE 1/4 Sec. 18, T. 15N., R. 4E. At the intersection of South Keystone Avenue and Pleasant Run Parkway S. Drive, at the Keystone Avenue bridge over Pleasant Run, set in the northwest wingwall of the bridge, 15 feet west of the centerline of the road, 3 feet above the sidewalk, 0.4 foot northeast of the southwest corner of the northwest wingwall, a chiseled cross. 738.423
DNR TBM PR 11	In Marion County, at Indianapolis, SE 1/4 Sec. 8, T. 15N., R. 4E., at the "Belt" switch yard, at the Indianapolis Union Railroad bridge over Pleasant Run, set in the top at the north corner of the east headwall of the bridge, 12 feet east of the east rail of the tracks, 2 feet below the tracks, 1.0 foot west of the east end of the headwall, a chiseled triangle. 778.451

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 140	In Marion County, at Indianapolis, E. 1/2 Sec. 8, T. 15N., R. 4E. At the English Avenue 90 foot concrete bridge over Pleasant Run, set in the top at the E end of the S. conc. guardrail, 26.5 feet south of the center line of the road, 12.4 feet west of the east end of the south guardrail of the bridge, 3.2 feet above the sidewalk, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 140 1960". 760.064
DNR TBM PR 3	In Marion County, N. 1/2 Sec. 2, T. 15N., R. 4E. About 4.5 miles southwest of Lawrence, about 0.25 mile south along Pleasant Run Parkway from its junction with 10th Street, at the junction of Pleasant Run Parkway and Springbrook South Drive, set in the top at the south end of the west headwall of a 6 foot box culvert over Springbrook, 120 feet north of the junction of the Springbrook South Dr., 23 feet west of the center line of the road, 12 feet south of an iron street light, 0.8 foot above the road, 0.65 foot north of the south end of the west headwall of the culvert, a chiseled triangle. 805.057
DNR TBM PR 4	In Marion County, SE 1/4 Sec. 35, T. 16N., R. 4E. About 4.0 miles southwest of Lawrence, about 0.3 mile north along East Pleasant Run Parkway South Drive from its junction with 10th Street (between 10th and 16th Streets), set in the top on the northeast wingwall of an 8 foot "V" shaped culvert over Warren Creek, 18 feet east of the center line of the road, 3.9 feet southwest of the northeast end of the northeast and southwest part of the V in the V-shaped culvert top, 0.7 foot below the road, a chiseled triangle. 815.104
DNR TBM PR 5	In Marion County, SE 1/4 Sec. 35, T. 16N., R. 4E. About 3.8 miles southwest of Lawrence, about 0.12 mile south along Edmonson Avenue from its junction with 16th Street, at a 10 foot box culvert over Warren Creek, set in the top at the north end of the west headwall of the culvert, 31 feet north of IP&L Company power pole #111-517A, 21 feet west of the center line of the road, 1.0 foot above the road, 0.8 foot south of the north end of the west headwall of the culvert, a chiseled triangle. 823.430
DNR BM MAR 138	In Marion County, E. 1/2 Sec. 35, T. 16N., R. 4E. About 3.65 miles SW of Lawrence, 0.05 mile S. along Shadeland Avenue from its intersection with 16th St., at a 6 foot box culvert over Warren Creek, set in the N. end of the W. headwall of the culvert, 30 feet W. of the center line of the south lane of traffic of Shadeland, 3 feet below the road, 1 ft. south of the N. end of the W. headwall, 0.6 ft. below the top of the headwall, a standard IFC&WRC BM tablet, stamped "MAR 1381960". 828.709

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR TBM PR 8	In Marion County, W. 1/2 Sec. 36, T. 16N., R. 4E. About 3.6 miles southwest of Lawrence, 0.36 mile east along East 16th Street from its intersection with Shadeland Avenue, at the East 16th Street 15 foot concrete bridge over Warren Creek, 600 feet east of Shortridge Road, set in the top at the west end of the north headwall, 13 feet north of the center line of the road, 0.6 foot above the road, the northwest corner of the north headwall, a painted red corner. 842.143
DNR TBM PR 9	In Marion County, W. 1/2 Sec. 36, T. 16N., R. 4E. About 3.6 miles southwest of Lawrence, 0.36 mile east along East 16th Street from its intersection with Shadeland Avenue, at the East 16th Street 15 foot concrete bridge over Warren Creek, 600 feet east of Shortridge Road, set in the top of the south guardrail of the bridge, 14 feet south of the centerline of the road, 7.3 feet east of the west end of the south guardrail, 3.5 feet above the road, a chiseled square. 844.641
DNR BM MAR 137	In Marion County, E. 1/2 Sec. 35, T. 16N., R. 4E. About 3.75 miles southwest of Lawrence, at the East 16th Street bridge over Pleasant Run, at a 36 inch sewer outlet at the SW corner of the bridge, set in the top of the "V" shaped top of the sewer, 50 feet east of the center line of East Pleasant Run Pkw. N. Dr., 35 feet south of the center of 16th Street 3 feet below the Parkway Drive, a standard IFC&WRC bronze benchmark tablet, stamped "MAR 137 1960". 813.655
INDOT BM MAR G 29	In Marion County, NE 1/4 Sec. 35, T. 16N., R. 4E. About 3.4 miles southwest of Lawrence, at the Shadeland Avenue 80 foot concrete bridge over Pleasant Run, set in the top of the west sidewalk of the bridge, 150 feet north of the center line of Pleasant Run Parkway, 30 feet west of the center line of the south lane of traffic of Shadeland, 25 feet north of the south end of the west guardrail of the bridge, 1.0 foot west of the east side of the sidewalk, 0.8 foot above the road, a standard ISHC benchmark tablet, stamped "MAR G 29". 828.815
USGS RP	In Marion County, NE 1/4 Sec. 35, T. 16N., R. 4E. About 3.4 miles southwest of Lawrence, at the Shadeland Avenue 80 foot concrete bridge over Pleasant Run, set in the top of the west bridge guardrail, 160 feet north of the center line of the south lane of traffic of Shadeland, 35 feet north of the south end of the west guardrail, 2.6 feet above the sidewalk, a chiseled arrow, marked "RP". 831.353

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 139	In Marion County, SW 1/4 Sec. 25, T. 16N., R. 4E. About 3.1 miles southwest of Lawrence, 0.13 mile east along East 21st Street from its intersection with Shadeland Avenue, at the East 21st Street 45 foot concrete arch bridge over Pleasant Run, set in the top at the west end of the north guardrail of the bridge, 15 feet north of the center line of the road, 9 feet above the roadway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 139 1960". 835.738
DNR TBM PR 10	In Marion County, SE 1/4 Sec. 25, T. 16N., R. 4E. About 3.0 miles southwest of Lawrence, 0.75 mile east along East 21st Street from its intersection with Shadeland Avenue; 0.25 mile west of the junction of North Franklin Road, at the East 21st Street 21 foot rectangular culvert over Warren Creek, set in the top at the east end of the north guardrail of the bridge, 45 feet west of the center line of Eastwood Place, 15 feet north of the center line of the road, 3.3 feet above the road, 0.4 foot west of the east end of the north guardrail, a chiseled triangle. 862.364
NGS BM Z 235	In Marion County, S. 1/2 Sec. 30, T. 16N., R. 5E. About 3.0 miles south of Lawrence, 1.5 miles east along East 21st Street from its intersection with Shadeland Avenue; and 0.4 mile west of it's intersection with North Post Road, at the Indiana State Police Post No. 52, set vertically in the east face of the southeast corner of a concrete block building, 68.5 feet north of the center line of 21st Street, 2.6 feet above the ground, 1.3 feet north of the southeast corner of the building, a standard USC&GS benchmark tablet, stamped "Z 235 1947". 880.248
DNR STA FIE C 3	In Marion County, SE 1/4 Sec. 8, T. 16N., R. 4E. At Indianapolis. From Monument Circle, north about 2.5 miles to the intersection of Fall Creek Parkway, northeast along Fall Creek Parkway about 3.6 miles to its intersection with east 46th Street, east along east 46th Street 0.2 miles to its intersection with Fall Creek Parkway North Drive and a standard Indiana Department of Natural Resources bronze tablet set in a concrete monument flush with the ground, 66.5 feet north of the centerline of 46th Street, 50.3 feet east of the centerline of Fall Creek Parkway North Drive, 12.5 feet south of the centerline of a turn lane, stamped "FIE C 3". 736.337

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR STA FIE C 7	In Marion County, N. 1/2 1/4 Sec. 9, T. 16N., R. 4E. At Indianapolis, from Monument Circle, north about 2.48 miles to the intersection of Fall Creek Parkway, northeast along Fall Creek Parkway about 3.6 miles to its intersection with east 46th Street, east on 46th Street to its intersection with Fall Creek Parkway North Drive, northeast along Fall Creek Parkway North Drive about 1.14 miles to a standard Indiana Department of Natural Resources bronze tablet set in a concrete monument flush with the ground, 34 feet south of the centerline of Fall Creek Parkway North Drive, 2250 feet west of the intersection of Emerson Way and Fall Creek, across the road from the drive to the residence of C.S. Wilson, about 600 feet southwest of the centerline of Drexel Ave., across the street from 5250 Fall Creek Parkway North Drive, stamped "FIE C 7". 735.776
DNR STA FIE C 17	In Marion County, NE 1/4 Sec. 2, T. 16N., R. 4E. At Indianapolis. From Monument Circle north about 2.48 miles to the intersection of Fall Creek Parkway, northeast along Fall Creek Parkway and State Road 37 about 4.93 miles to its intersection with 56th Street, east on 56th Street about 0.52 miles to its intersection with Fall Creek Road, northeast along Fall Creek Road about 2.23 miles to a standard Indiana Department of Natural Resources bronze tablet set in a concrete monument flush with the ground, 33 feet east of the centerline of Johnson Road, 28 feet north of the centerline of Fall Creek Road, about 1800 feet west of centerline intersection of Fall Creek Road and Road #100, stamped "FIE C 17". 749.444
DNR STA FIE E 22	In Marion County, SE 1/4 Sec. 35, T. 17N., R. 4E. At Indianapolis, from Monument Circle north about 2.48 miles to the intersection of Fall Creek Parkway, northeast along Fall Creek Parkway about 3.6 miles to its intersection with 46th Street, east on 46th Street about 0.2 miles to its intersection with Fall Creek Parkway North Drive, northeast along Fall Creek Parkway North Drive about 4.8 miles to a standard Indiana Department of Natural Resources bronze tablet set in a concrete monument flush with the ground, 29 feet south of the centerline of Fall Creek Parkway North Drive, 265 feet southwest of the intersection of Fall Creek Parkway North Drive and Shafter Road, stamped "FIE E 22". 752.551

MARION COUNTY
INDIANAPOLIS EAST QUAD

MARK	ELEVATION FEET (NGVD 29)
DNR STA LI TT A 18	In Marion County, SE 1/4 Sec. 10, T. 15N., R. 4E., From the intersection of south Arlington Avenue and Brookville Road, south on Arlington Avenue 0.1 mile to conc. monument located on northwest end of Arlington Avenue bridge over the Conrail tracks, 2.3 feet west of the west curb of Arlington Avenue, 3.2 feet northwesterly of west corner of west conc. bridge abutment. A standard D.N.R. Div. of Water control station tablet in a conc. post stamped "LI TT A 18". 844.109
DNR STA LI TT A 26	In Marion County, S. 1/2 Sec. 6, T. 15N., R. 5E., from the intersection of east Washington Street (U.S. 40) and Fenton Avenue south on Fenton Avenue 0.2 miles; also just north of the Conrail tracks, conc. monument located on east side of avenue, 18.8 feet east of the east edge of Fenton Avenue, 7.9 feet north of the N. rail of the tracks. A standard D.N.R. Div. of Water control station tablet in a conc. post stamped "LI TT A 26". 861.264

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD 29)
NGS BM X 78	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 3, T. 16N., R. 3E. On Michigan Road about 2.1 Mi. S.E. from the intersection of U.S. Hwy. 421 with 71st St. in Augusta, and 0.1 mile N.E. of the intersection with Kessler Blvd., at the 75 foot conc. arch bridge over Little Eagle Cr. Set in top of the west wingwall, 16 feet southwest of the center line of the highway and about level with the bridge floor, a standard USC&GS bronze disk stamped "X 78 1946". 761.547
DNR BM MAR 14	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 5, T. 15N., R. 3E. At the N. Roena Street Bridge over Eagle Creek in Indianapolis, at about 4200 West Vermont Street. On the 300 foot concrete bridge, on the south end of the east abutment, 7 ft. below the top of the east end of the south handrail, a standard IFC & WRC bronze benchmark tablet stamped "MAR 14". 717.670
DNR BM MAR 16	In Marion County, Indianapolis West Quad, NE 1/4 Sec. 8, T. 15N., R. 3E. On the Conrail Railroad Bridge over Eagle Creek, about 400 feet south of 3500 West Washington Street, about 800 feet east of the railroad overpass over U.S. Highway 40, on the northwest wingwall of the bridge, 5 feet north of the north rail, 1.6 feet below the rails, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 16". 715.058
DNR BM MAR 17	In Marion County, Indianapolis West Quad, NW, 1/4 Sec. 9, T. 15 N., R. 3E. On the Conrail Railroad Bridge over Little Eagle Creek, about 400 feet south of the 3350 West Washington Street, on the northeast concrete wingwall, 0.9 foot below the concrete dock rail, 1.4 foot below top of rail, 5 feet north of the north rail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 17". 710.882
DNR BM MAR 19	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 9, T. 15N., R. 3E. On the Pennsylvania Railroad Bridge over Eagle Creek, midway between Washington and Morris Streets, on the concrete base of the south handrail, 4 feet from the west end, 7.7 feet south of the south rail, 1.0 foot below the tracks, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 19". 711.082
NGS BM D 79	In Marion County, Indianapolis West Quad, S. 1/2 Sec. 26, T. 16N., R. 3E. In Indianapolis; On the northwestern Avenue Bridge over Fall Creek, 33 feet east of the center line of Northwestern Avenue, set in the top of the north end of the east railing of the stone and concrete bridge, 50 feet south of the center line of West Fall Creek Parkway, and about 4 feet above the sidewalk, a standard USC & GS bronze disk stamped "D 79 1946". 714.300

MARION COUNTY
INDIANAPOLIS WEST QUAD

ELEVATION
FEET
(NGVD '29)

MARK

DNR BM
MAR 25 In Marion County, Indianapolis West Quad, SW 1/4 Sec. 26, T. 16N., R. 3E. At the south end of the road south from Fall Cr. Parkway along the east bank of the Indianapolis Water Company Canal, at the canal crossing over Fall Creek, 300 feet north of Fall Creek, at the spillway allowing flow from the canal into Fall Creek, on the southwest corner of the northwest wall of the spillway, 15 feet northeast of the northeast bank of the canal, 1 foot northeast of the woven wire fence across the crest of the spillway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 25". 711.264

DNR BM
MAR 26 In Marion County, Indianapolis West Quad, SE 1/4 Sec. 27, T. 16N., R. 3E. On the Indianapolis Union Railway Bridge over Fall Creek, 0.5 mile downstream from the Northwestern Avenue Bridge, on the northeast end of the northwest abutment, 3.4 foot north-east of the northeast rail, 0.7 foot below the top of the rail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 26". 711.442

DNR BM
MAR 28 In Marion County, Indianapolis West Quad, E. 1/2 Sec. 26, T. 16N., R. 3E. At the Capitol Avenue Bridge over Fall Cr. 51 feet southeast of the center of the intersection of Capitol Avenue and Fall Creek Parkway, 4.0 feet above the sidewalk, on the east handrail, 1.9 feet south of the north end, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 28". 718.584

DNR BM
MAR 29 In Marion County, Indianapolis West Quad, E. 1/2, Sec. 26, T. 16N., R. 3E. At the Illinois Street Bridge over Fall Creek, on the floodwall along the north bank of Fall Creek, 81 feet south of the center line of Fall Creek Parkway, 3.6 feet east of the east handrail of the bridge, 4.2 feet below the top of the north end of the handrail, 1.8 feet above the ground, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 29". 715.340

USGS BM
TT 8 DWP In Marion County, Indianapolis West Quad, W. 1/2, Sec. 25, T. 16N., R. 3E. On the Meridian Street Bridge over Fall Creek, in the west handrail, at the north end, 1.9 feet below the top of the handrail, set horizontally, a standard U.S. Geological Survey bronze benchmark tablet stamped "TT 8 DWP". 718.518

DNR BM
MAR 31 In Marion County, Indianapolis West Quad, N 1/2, Sec. 25, T. 16N., R. 3E., at the Central Avenue Bridge over Fall Creek, on the floodwall along the north bank of Fall Creek, 66 feet S. of the center line of Fall Creek, 39 feet west of the center line of Central Avenue, 6 feet west of the west handrail of the bridge, 7.0 feet below the top of the handrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 31". 715.419

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
NGS BM D 43	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 18, T. 16N., R. 4E. Near the Southwest corner of the Indiana State Fairgrounds, about 56 yards north of the center of the intersection of the abandoned railroad and 38th Street, in the concrete water table at the east side of the old Boulevard station, 7 yards west of where the west rail was, and 1 foot above the sidewalk. A standard USC&GS bronze disk set vertically and stamped "D 43 1934". 736.613
DNR BM MAR 36	In Marion County, Indianapolis, West Quad, SE 1/4, Sec. 18, T. 16N., R. 4E. On the 39th Street (also referred to as Millersville Drive) Bridge over Fall Creek, on the north handrail, 3.4 feet from the east end, 2 feet above the roadway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 36". 734.285
USED TBM 10	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 2, T. 15N., R. 3E. At the Washington Street Bridge over White River, 50 feet north of the center line of Washington Street, 14 feet west of the center line of Blake Street, on the floodwall northward from the east end of the bridge, a lead plug. 703.640
DNR BM MAR 52	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 2, T. 15 N., R. 3E. At the Washington Street Bridge over White River, on the floodwall northwestward from the west end of the bridge, 39 feet north of the center line of Washington Street about 14 feet northwest of the west end of the north handrail of the bridge, a standard Indiana Flood Control and Water Resources Commission bronze benchmark table stamped "MAR 52". 702.745
DNR BM MAR 54	In Marion County, Indianapolis West Quad, NW 1/4, Sec. 3, T. 15 N., R. 3E. On the Michigan Street Bridge over White River, on the northwest wingwall, 33 feet northeast of the center line of the White River Parkway, 5 feet northwest of the west endpost of the north handrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 54". 704.907
DNR BM MAR 55	In Marion County, Indianapolis West Quad N1/2, Sec. 3, T. 15N., R. 3E. At the Michigan Street Bridge over White R., on the SE wingwall, 32 feet south of the center line of Michigan Street, 5 feet south of the east end of the south handrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 55". 704.885

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 58	In Marion County, Indianapolis West Quad, S 1/2, Sec. 34, T. 16N., R. 3E. At the Union Railroad Bridge over White River, 0.4 mile north of the 10th Street crossing, on the west end of the south abutment, one foot west of the 4 foot square concrete base of the southwest bridge seat, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 58". 700.343
USED TBM 14	In Marion County, Indianapolis West Quad, S 1/2, Sec. 34, T. 16N., R. 3E. Near the Indianapolis Union Railroad Bridge over White River, 0.4 miles N.E. of the Tenth St. crossing, on the West corner of a concrete manhole structure., 52 feet S.W. of the centerline of Speedway Ave., 74 feet N.W. of the center line of the tracks, chiseled square. 696.671
DNR BM MAR 60	In Marion County, Indianapolis West Quad, E 1/2, Sec. 33, T. 16N., R. 3E., at the West Sixteenth Street Bridge over White River, set in the west end of the south walkway, 3.0 feet east of the west end of the bridge, 0.8 foot north of the south hand-rail, a standard IFC&WRC bronze benchmark tablet, stamped "MAR 60". 713.269
NGS BM E 79	In Marion County, Indianapolis West Quad, Near the center of Sec. 35, T. 16N., R. 3E. At the intersection of West 16th Street and Northwestern Avenue, at a concrete bridge over the Indianapolis Water Company Canal, set in the top of the hand-rail, 73 feet south of the center line of West 16th Street, 39 feet east of the center line of Northwestern Avenue, 3.1 feet above the sidewalk, 1.1 feet southwest of the northeast edge of the east handrail, 0.7 foot east of the west edge of the east handrail, a USC&GS standard disk, stamping has been obliterated. 715.756
NGS BM H 79	In Marion County, Indianapolis West Quad, E 1/2, Sec. 34, T. 16N., R. 3E. At the West 16th Bridge over Fall Creek, in the top of the west end of the north railing of the 4 span concrete arch bridge, 31 feet north of the center line of the street, and about 3 feet higher than the sidewalk. A USC&GS standard disk, stamped "H 79 1946". 711.839
INDOT BM MAR G 27	In Marion County, Indianapolis West Quad, E. 1/2, Sec. 33, T. 16N., R. 3E. On the West 16th Street Bridge over White River, set in the west end of the north walkway, 0.5 foot south of the north handrail a standard Indiana State Highway Commission bronze tablet, stamped "MAR G 27". 713.089

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 61 RESET	In Marion County, Indianapolis West Quad, Near the N.E. corner of Sec. 33, T. 16N., R. 3E. About 0.5 Mi. N. on White River Parkway from its junction with West Sixteenth Street at Indianapolis to a 2 foot pipe culvert under the road, set in the top at the southwest end of the southeast concrete headwall, 65.0 feet southeast of the center line of the road, 12.0 feet below the road, 2.2 feet northeast of the southwest end of the southeast headwall, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 61 RESET 1962". 695.555
DNR TBM DRC 8	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 30, T. 16N., R. 3E. At the Allison Street Bridge over Dry Run, set in the top of the northwest handrail of the bridge, 190 feet southwest of the intersection of McCray and Allison Streets, 18 feet northwest of the center line of Allison Street, 10.5 feet northeast of the southwest end of the northwest handrail, 3.0 feet above the roadway, at the west corner of the handrail post, a chiseled square. 741.499
DNR BM MAR 157	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 30, T. 16N., R. 3E. At the Allison Street Bridge over Dry Run, set in the top of the northwest handrail of the bridge, 190 feet southwest of the intersection of McCray and Allison Streets, set in the top of the northwest handrail of the bridge, 18 feet northwest of the center line of the street, 11 ft. southwest of the northeast end of the northwest handrail of the bridge, 3.0 feet above the roadway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 157 1961". 741.502
DNR TBM MD 2	In Marion County, Indianapolis West Quad, NE 1/4, Sec. 30, T. 16N., R. 3E. At the intersection of Georgetown Road and 30th Street, in the southeast quarter of the intersection, set in the top of a wall at the south edge of a service station; at the north edge of a grocery store parking lot, 150 feet south of the center line of 30th Street, 60 feet east of the center line of Georgetown Road, 1.4 feet above the parking lot, 0.7 foot west of the east end of the short wall (between sidewalk and drive), a chiseled triangle. 744.683

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
USED TBM 39	In Marion County, Indianapolis West Quad, S.E. 1/4, Sec. 35, T. 17N., R. 3E. At the abandoned bridge at White River and East 64th Street, set in the top of the wingwall, 24 feet south of the center line of East 64th Street, 2 feet south of the north northeast edge of the southeast wingwall, 0.5 foot west northwest of the east southeast edge of the southeast wingwall, a chiseled square. 724.221
USGS RM 5	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 36, T. 17N., R. 3E. Across the street from 6340 Winthrop Avenue or Broad Ripple Ave. (old S.R. 431), set in the top of a conc. post, 68 feet east of the northeast corner of the Indianapolis Water Company building, 43 feet east southeast of the southeast corner of the stream gage shelter house, 17 feet southeast of the northwest end of the west bank retaining wall, 8 feet southwest of the northeast edge of the wall, level with the ground, a USGS gaging station tablet. 716.256
DNR BM MAR 78	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 36, T. 17N., R. 4E. At the Broad Ripple High School, set vertically in the side of the building, 124 feet east of Compton Street, in the west side of the high school, 24.5 feet south of the north side of the school building, 1.8 feet above the ground, an Indiana Flood Control and Water Resources Commission standard bronze benchmark tablet, stamped "MAR 78". 734.944
NGS BM B 43	In Marion County, Indianapolis West Quad, E 1/2 Sec. 1, T. 16N., R. 3E. At the abandoned railway bridge over 59th St. or Kessler Boulevard East, in the southwest corner of the aband. bridge, set in the top of the south bridge seat, 17 feet south of the center line of 59th Street, 7.5 feet west of the old location of the west west rail, 4.1 feet lower than the level of the old tracks, and 0.7 foot south of the north face of the south bridge seat, a USC&GS BM tablet, stamped "B 43 1934". 736.931
DNR BM MAR 20 RESET	In Marion County, Indianapolis West Quad, SW 1/4, Sec. 9, T. 15N., R. 3E. At the West Morris Street bridge over Eagle Creek, set in the northeast corner of the bridge, 32 feet north of the center line of W. Morris Street, 14 feet west of the east end of the north handrail, 2.8 feet below the top of the handrail, 0.2 foot north of the north face of the north handrail, set in top of the handrail base, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 20 RESET". 701.190

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
USED TBM 19	In Marion County, Indianapolis West Quad, NW 1/4, Sec. 27, T. 16N., R. 3E. At the 30th Street Bridge over White River, set in the top of the post, 68 feet west of the center line of White River Parkway, 43 feet south southwest of the center line of 30th Street, at the north northwest corner of the post at entrance of southeast steps, 3.5 feet above the sidewalk, a chiseled cross. 716.063
DNR BM MAR 69	In Marion County, Indianapolis West Quad, N 1/4E Sec. 10, T. 16N., R. 3E., in Rocky Ripple, at the bend in Riverview Drive before being West 54th Street, on the extended center line southwest of the straight part of the road after the bend, set in the top of a concrete post level with the ground, 27 feet east of the center line of the fireplace (Sign on fireplace "O. L. Stewart Decorator Painter of Fine Homes) at residence 5374 Riverview Drive, 20 feet west of the center line of the road, 14 feet north of pole 58-333B, 1.0 foot east of a small picket fence, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 69". 707.185
DNR BM MAR 72 RESET	In Marion County, Indianapolis West Quad, NE 1/4, Sec. 2, T. 16N., R. 3E., at the Kessler Boulevard Bridge over White River, set in the top of the northeast wingwall of the bridge, 33 feet north of the center line of Kessler boulevard, 3.3 feet east of the west face of the northeast wingwall, 1.7 feet northeast from the northeast corner of the north handrail, 0.6 foot below the bridge sidewalk, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 72 RESET." 725.614
DNR TBM LEC 1	In Marion County, Indianapolis West Quad, NW 1/4, Sec. 5, T. 15N., R. 3E. About 0.5 mile west along West Tenth Street from its intersection with the Conrail Railroad to the West Tenth Street two-span concrete bridge over Little Eagle Creek, then 75 feet south along the creek to a wooden RR bridge over Little Eagle Creek, set in the west face of the east retaining wall of the bridge, 6 feet south of south rail, 5.8 feet north of the lowest south face of the southeast retaining wall, 4 feet below the top of the south rail, a railroad spike through an aluminum tag, stamped "TBM LEC 1, 1959." 718.176
INDOT BM MAR G 20	In Marion County, Indianapolis West Quad, SE 1/4, Sec. 32, T. 16N., R. 3E., About 0.5 mile west along West Tenth Street from its intersection with the Conrail Railroad; set in the top of the northwest wingwall of the West Tenth Street two-span concrete girder bridge over Little Eagle Creek; 27 feet north of center line of roadway; 0.5 foot west of the east face of the northwest wingwall; 2.7 feet below top of the north guard rail; an Indiana State Highway bronze benchmark tablet, stamped "MAR G20." 722.140

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR TBM LEC 4	In Marion County, Indianapolis West Quad, SE 1/4, Sec. 32, T. 16N., R. 3E. About 0.6 mile northwest along the Conrail tracks from their intersection with West Tenth Street to a wooden railroad bridge over Little Eagle Creek, set in the top of the south end of the east bridge seat, 7.2 feet below the rail level, 5 feet south of the south rail, 1.8 feet west of the west face of the east retaining wall, a chiseled triangle. 719.964
DNR TBM DRC 5	In Marion County, Indianapolis West Quad NW 1/4 Sec. 31, T. 16N., R. 3E. Set in the conc. base of the West Indianapolis Motor Speedway chain link property fence near the Georgetown Road single span conc. bridge over Dry Run: 1.7' above sidewalk, 0..1' east of west face of concrete wall; 31.5' east of center line of Georgetown Road, 77.3' North of power/light pole #69057B 7.6' So. of southerly most point of east bridge wheel guard, and 5.8' East of east face of curb. A chiseled triangle. 732.178
USGS RM 3	In Marion County, Indianapolis West Quad, NW 1/4, Sec. 32, T. 16N., R. 3E. About 1.6 miles west along West Sixteenth Street from the West 16th Street bridge over White River to a three-span concrete bridge over Little Eagle Creek, set in the top of the south end of the west pier of the bridge, 42 feet south of center line of the roadway, 7.8 feet below the top of south handrail, a standard USGS Water Resources bronze reference mark tablet, not stamped. 721.725
INDOT BM MAR 35	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 32, T. 16N., R. 3E. About 1.6 miles west along West Sixteenth St. from West 16th Street bridge over White River to a three-span concrete bridge over Little Eagle Creek, set in the top of the west end of the northwest wingwall, 40.3 feet north of the center line of the roadway, at the west end of the north hand-rail, at the sidewalk level, ISHC bronze benchmark tablet, stamped "MAR 35". 726.866
USGS RM 2	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 32, T. 16N., R. 3E. (Speedway), 1.6 miles west along West Sixteenth Street from West 16th Street bridge over White River to a three-span concrete bridge over Little Eagle Creek, at the southwest corner of the bridge, set in the top of the first step above the bridge walkway, 39.6 feet south of the center line of the street, 2.0 feet east of the west end of the south guardrail, 2.0 feet above the roadway, a standard USGS Water Resources bronze R.M. tablet, stamped "2". 727.870

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 126	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 32, T. 16N., R. 3E. About 1.6 miles west along West Sixteenth Street from the West 16th Street bridge over White River to a three-span concrete bridge over Little Eagle Creek, at the northeast corner of the bridge, set in the top of a concrete spillway headwall at the northeast corner of the bridge, 11 feet north of the north edge of the bridge, 5 feet above the base of the spillway, 1.2 feet west of the east end of the north guardrail of the bridge, 0.7 foot south of the north edge of the top of the headwall of the spillway, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 126 1959". 725.052
INDOT BM MAR G 19	In Marion County, at Indianapolis, SW 1/4 Sec. 32, T. 16N., R. 3E. About 0.65 mile west along West Tenth Street from its intersection with the CSX Railroad to a two-span concrete girder bridge over Dry Run, set in the to of the northwest wingwall, 27.5 feet north of center line of the roadway, 2.7 feet below top of north guardrail, 0.7 foot east of west face of guardrail, an ISHC bronze benchmark tablet, stamped "MAR G19." 723.247
DNR TBM DRC 1	In Marion County, at Indianapolis, SW 1/4 Sec. 32, T. 16N., R. 3E. About 0.65 mile west along West Tenth Street from its intersection with the CSX Railroad to a two-span concrete girder bridge over Dry Run, thence 100 feet north along the creek to a wooden CSX Railroad bridge over Dry Run, set in the top of the north end of the west concrete bridge seat, 3.5 feet north of the north rail, 2.3 feet below the top of the rail, 0.8 foot west of the east face of the bridge seat, a chiseled triangle. 720.125
DNR TBM DRC 2	In Marion County, at Indianapolis, SW 1/4 Sec. 32, T. 16N., R. 3E. About 2.0 miles west along West Sixteenth Street from the West 16th Street Bridge over White River to a T-road south, then 0.15 mile south to the intersection of T-road south and the Conrail Railroad, thence 175 feet southeast along railroad tracks to a single span concrete railroad bridge over Dry Run, set in the top of south end of west bridge seat, 8.9 feet south of the south rail, 1.4 feet below the top of the rail, 0.5 foot west of the east face of the bridge seat, a chiseled triangle. 725.536
DNR TBM DRC 3	In Marion County, at Indianapolis, W 1/2 Sec. 32, T. 16N., R. 3E. About 1.9 miles west along West Sixteenth Street from West 16th Street bridge over White River to a three-span concrete bridge over Dry Run, set in the top of the west pier, 41.5 feet south of the center line of West 16th Street, 23.6 feet east of the west end of south guard rail, 4.9 feet below the top of the guard rail, 0.4 foot north of the south end of the pier, a chiseled triangle. 727.097

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 62 RESET	In Marion County, Indianapolis West Quad, W 1/2 Sec. 27, T.16N., R.3E. At the north junction of Burdsal Parkway and White River Parkway, set in the top of a 2-foot pipe culvert under White River Parkway, 150 feet north of the extended center line of Burdsal Parkway, 75 feet east of the center line of White River Parkway, 15.0 feet below the road, 2.0 feet south of the north end of the headwall, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 62 RESET 1962". 696.082
DNR BM MAR 63	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 27, T. 16N., R. 3E. At the Thirtieth Street Bridge over White River, set in the top of the southwest concrete guardrail, 43 feet south-southwest of the center line of the road, 8 feet west-northwest of the east-southeast face of the west-northwest abutment, 3.5 feet above the sidewalk, 1.2 feet east-southeast of the entrance to the southwest steps, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 63". 716.294
DNR BM MAR 160	In Marion County, Indianapolis West Quad, SE 1/4 Sec. 20, T. 16N., R. 3E., at the U.S. 52 concrete arch bridge over Little Eagle Creek, set in the top of the northwest end of the northeast concrete guardrail of the bridge, 27.3 feet northeast of the center line of the highway, 3.2 feet above the top of the northeast concrete sidewalk, 1.85 feet southeast of the northwest face of the northeast guardrail, a standard Indiana Flood Control and Water Resources Commission benchmark tablet, stamped "MAR 160 1962". 744.160
DNR TBM LEC 6	In Marion County, Indianapolis West Quad, N 1/2 Sec. 20, T.16N., R.3E At the Conrail Railroad bridge over Little Eagle Creek in Northwestern Indianapolis, 0.4 mile northeast of the U.S. 52 overpass over the Conrail tracks, and set in the top of the west end of the south concrete abutment of the bridge, 5.3 feet west of the west rail of the tracks, 1.8 feet below the top of the rails, 0.7 foot south of the north face of the south abutment, a chiseled triangle. 748.019
DNR TBM LEC 7	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 20, T. 16N., R. 3E. At the West 38th Street 3-span Conc. bridge over Little Eagle Creek, set in the top at the east end of the S. conc. guardrail base of the bridge, 19.0 ft. S. of the center line of the east-bound lane of the road, 3.4 feet west of the east end of the south concrete guardrail base, 0.95 foot above the road, 0.5 foot north of the north face of the south guardrail, a chiseled triangle. 756.077

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 162	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 17, T. 16N., R. 3E. At the West 38th Street 3-span concrete bridge (Pike Township bridge #84) over Little Eagle Creek, set in the top of the west end of the north concrete guardrail base, 18 feet north of the center line of the west bound lane, 4.8 feet east of the west end of the north guardrail base, 0.9 foot above the road, 0.5 foot south of the south face of the west end of the north concrete guardrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 162 1962". 757.242
DNR BM MAR 164	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 5, T. 16N., R. 3E. At the West 56th Street bridge over Guion Creek, set in the top of the north concrete guardrail of the bridge, 16.0 feet north of the center line of the road, 14.7 feet west of the east end of the north guardrail, 3.4 feet above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 164 1962". 799.960
DNR TBM FC 2	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 20, T. 16N., R. 3E. In the Eagledale housing development, one block north along Patricia Street from its junction with West 30th Street to the Farrington School (Public School #61), set in the top near the center of the concrete headwall of a 9 inch storm drain on the west bank of Falcon Creek, about 370 feet north of the 30th Street bridge over Falcon Creek, 79.5 feet east of the east entrance doors to the school building, 18.5 feet southeast of a telephone pole carrying 3 transformers, 2.0 feet below the center line of the paved drive around the school building, 1.6 feet north of the south face of the headwall, a chiseled triangle. 736.685
DNR BM MAR 165	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 20, T. 16N., R. 3E. In the Eagledale housing development, at the Thrush Drive bridge over Falcon Creek, set in the top of the west end of the south concrete sidewalk of the bridge, 18.5 feet south of the center line of the road, 3.6 feet south of a point where the south sidewalk joins the south curb, 1.4 feet east of the west end iron pipe guardrail post of the south iron pipe guardrail, level with the center line of the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 165 1962". 743.013

MARION COUNTY
INDIANAPOLIS WEST QUAD

ELEVATION
FEET
(NGVD '29)

MARK

DNR BM MAR 167	In Marion County, Indianapolis West Quad, NE 1/4 Sec. 19, T. 16N., R. 3E. In the Eagledale housing development, about 1 & 1/2 blocks east along West 36th Street from its junction with Georgetown Road to a dead end at Falcon Creek, set in the top at the center of a concrete headwall of a 12 inch cast iron pipe culvert on the west bank of Falcon Creek, 31 feet south of the extended center line of West 36th Street, 3.3 feet south of the north face of the headwall, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 167 1962". 747.145
DNR STA LEA B1	In Marion County, Indianapolis West Quad, SE 1/4, Sec. 5, T. 15N., R. 3E. In the E. end of S. walkway of conc. bridge over Little Eagle Creek on Cossell Rd: 143.06 feet W. of nail & bottlecap in P/P 69 592-A; 106' SW of 21 inch Pine Tree; 77.08 feet SW of nail & bottlecap in twin trunked 6 inch cherry tree, 68.13 feet SE of nail & bottlecap in P/P 28 529-A, 11.29 feet NE of an "X" in top of concrete a standard DNR Div of Water BM tablet stamped "LEA B1". 716.59
DNR STA LEA B2	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 5, T.15N., R.3E. At the Holt Road Bridge over Little Eagle Creek. At the NW corner of the bridge on the NW corner of the concrete apron: 44.2 feet SW of P.K. nail & bottlecap in curb joint on east side of Holt Road; 40.2 feet W of P.K. nail in curb joint; 47.4 feet NW of cut "X" in cover plate for bridge joint; 7.5 feet SW of cut "X" in top of 1st guard rail post N. of N. end of concrete apron. A standard DNR Div of Water bronze disk stamped "LEA B 2". 721.21
DNR STA LEA B3	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 32, T. 16N., R. 3E. At the 16th. Street underpass below the Conrail Railroad on the east side of the Indianapolis Motor Speedway Golf Course. Near the NW corner of the Conrail Railroad Bridge over 16th Street; 14.71 feet NE of ISHC BM MAR 36; 21.83 feet NE of cut "X" on base bolt for handrail on the NW corner of bridge, 95.49 feet NW of cut "X" on base bolt for handrail, on the SE corner of bridge 2nd post from south end. 41.29 feet NW of cut "X" on base bolt of hand rail on the NE corner of bridge, 59.22 feet Westerly of nail and bottlecap in telephone pole. A standard DNR Div. of Water bronze disk set in concrete post stamped "LEA B 3". 734.90
DNR STA LEA B4	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 29, T. 16 N., R. 3E. At the SW corner of the intersection of West 30th Street and Conrail RR.: 14 ft. S. of S. edge of W. 30th. St. and 25 ft. W. of W. rail; 25.0 ft. SE of nail & bottlecap in light pole on S. side of 30th St.; 60.1 ft. SE of nail & bottlecap in power guy pole 32 428A on N. side of 30th St.; 18.4 ft. SW of cut X in bolt on RR crossing on E. side of gravel access road, 49.8 ft. W. of meter pole on east side of Conrail, 30 ft. NE of P/P 348 426-B. Under about 2 feet of railroad fill. A standard DNR bronze disk set in concrete post, stamped "LEA B 4". 740.33

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR STA LEA B5	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 17, T. 16N., R. 3E. At the south corner of the S. bound I-65 bridge over West 38th Street: 43.8 ft. SE and across the highway from a PK nail set in 2nd handrail joint NW from SE end of bridge; 50.6 ft. SW and across the highway from cut X on top of handrail; 62.4 ft. SW of RR spike set in concrete apron; 7.7 ft. SE of cut "X" in west end of south wingwall; 21.8 ft. NW of cut "X" on west side of aluminum light pole base on south side of wingwall. In the SE Wingwall of the Bridge, a standard DNR Div. of Water tablet stamped "LEA B5". 786.12
DNR STA LEA B6	In Marion County, Indianapolis West Quad, NE 1/4 Sec. 18, T. 16N., R. 2E. At the southeast corner of the south concrete apron of the Georgetown Road bridge over I-65: 6.7 feet south-west of cut "X" on top of guard rail base bolt; 2.6 feet west of cut "X" in tire bumper; 12.7' north of cut "X" in corner of concrete drain; 27.3' NE of RR spike set in crack of asphalt and concrete; and 53.2' southwest from an unstamped DNR Tablet. A standard DNR Div. of Water tablet stamped "LEA B6". 795.16
DNR STA CCA C1	In Marion County, Indianapolis West Quad, NW 1/4 Sec. 16, T. 16N., R. 3E. About 475 feet north along Kessler Boulevard North Drive from its intersection with the center line of West 44th Street: 66.3 feet north of power pole 48 360B; 37.37 feet west-erly of a 36 inch Oak tree; and 14 feet east of east edge of Kessler Boulevard North Drive. A standard DNR Div. of Water Tablet stamped "CCA C1". 733.07
DNR STA CCA C2	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 4, T. 16N., R. 3E. In the NE corner of the intersection of Cooper Road and Kessler Boulevard West Drive: 42.7 feet southerly of a PK nail in power pole #114 330-A; 10.8 feet west of cut "X" in bolt of concrete base of light pole; 78.9 feet northwest of "X" cut in the bolt of concrete base of light pole in SE corner of inter-section; 97.6 feet northeast of cut "X" in bolt of concrete base of light pole in SW corner of intersection; and 57.18 feet east of cut "X" in bolt of concrete base of light pole in NW corner of intersection. Set in a concrete post, a standard DNR Div. of Water Tablet stamped "CCA C 2". 774.49
DNR STA CCA C3	In Marion County, Indianapolis West Quad, SE 1/4 Section 4, T. 16N., R. 3E. About 2000 feet east along Kessler Boulevard West Drive from its intersection with Kessler Boulevard North Drive: 83.5 feet SE of power pole #98 331-A; 37 feet southeast of concrete pillar; 28.3 feet south of the wrought iron fence around the Cemetery; 37.2 feet southwest of another concrete pillar; 195.5 feet southwest of power pole #3 331-A; 11.9 feet north of north edge of road. 89.5 feet northwest of a 20 inch Elm tree. Set in a concrete post, a standard DNR Div. of Water Tablet stamped "CCA C 3". 774.44

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR STA CCA D1	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 22, T. 16N., R. 3E. About 1300 feet north along White River Parkway from its intersection with 30th Street on the West side of the Parkway: 46.9 feet southeast of a nail and cap in a 6 inch Cherry tree; 41.5 feet northeast of a 36 inch Sycamore tree; 69.9 feet northwest of another 36 inch Sycamore tree. Set in a concrete post, a standard DNR Div. of Water bronze disk, stamped "CCA D 1". 708.75
DNR STA CCA A5	In Marion County, Indianapolis West Quad, SE 1/4 Sec. 33, T. 17N., R. 3 E. In the SW corner of intersection of Grandview Dr. and W. 63rd Street; 136.1 feet SW of a nail & bottlecap in P/P 15-303A; 48.8 feet westerly of a nail & bottlecap in an 18" Box Elder; 82.4 feet NW of a nail and cap in P/P 16-303-A; 60.5 NW of a nail & bottlecap in P/P 14-303-A; 14.0 feet SE of a nail & bottlecap in P/P 159 302-A. Set in the south end of the concrete curb. A standard DNR Div. of Water bronze disk stamped "CCA A5" 781.01
DNR STA CCA A6	In Marion County, Indianapolis West Quad, S 1/2 Sec. 3, T.16N., R.3E. On the West side of Grandview Dr., about 390 feet S. of the intersection of Kessler Blvd. and Grandview Dr. and about 180 feet N. of the intersection of Collingwood Dr. and Grandview Dr: 111.4' feet SW of a nail & bottlecap in a 15 inch Sweet Gum tree; 38.6 feet westerly of a nail & bottlecap in a 10 inch Cherry tree; 119.6 feet N. of a nail & bottlecap in P/P 132 338-A; 45.5 feet S. of a nail & bottlecap in P/P 135 332-A; 53.8 feet SE of a cut X on top nut of fire hydrant. A standard DNR Div. of Water bronze disk set in concrete post and stamped "CCA A 6". 774.61
DNR STA CCA D2	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 21, T. 16N., R. 3E. About 3200 feet east along West 30th Street from its intersection with Lafayette Road, on the north side of the street, between the sidewalk and the street: 141.5 ft. east of a nail and cap in light pole #138 430-A on W. side of Medford Avenue; 49.8 ft. southeast of a 10 inch Maple tree, 66.9 feet southwest of southwest corner of first step of walk to "Seventh and Eighth United Christian Church" 71.0 feet west of nail and cap in light pole #139 430-A; 64.6 feet northeast of a nail and cap in Power and Light pole #51 430B. On the south side of West 30th St. and set in a concrete post, a DNR Div. of Water bronze disk stamped "CCA D2". 751.09
DNR STA FIW A6	In Marion County, Indianapolis West Quad, SE 1/4 Sec. 18, T. 16N., R. 4E. At the intersection of Fall Creek Parkway and the Norfolk Southern Railroad: 55 ft. N. of the center line of Fall Creek Pkwy.; 13.4 ft. E. of the E. rail; 11 ft. N. of the N. curb; 10.8 ft. N. of a punch hole in N. bolt of a RR crossing signal; 100.0 ft. SE of Ref. Mark #2; 17.8 ft. S. of a PK nail and cap in power pole; 5.1 ft. NW of a PK nail and cap in power pole. A standard DNR Div. of Water tablet in a concrete post stamped "FIW A-6". 739.146

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR STA TT A7	In Marion County, Indianapolis West Quad, NE 1/4 Sec. 6, T. 16N., R. 3E. At the intersection of Kessler Blvd. East Drive and Evanston Street in the SW corner of the intersection: 17.5 feet west of the extended center line of Evanston Street; 36.4 feet south of the center line of Kessler Blvd.; 17.5 feet SW of center of a manhole cover; 17.4' SE of the center of a catch basin; and on the east end on the center line of the sidewalk a chiseled cross. 738.737
DNR STA TT A8	In Marion County, Indianapolis West Quad, NE 1/4 Sec. 1, T. 16N., R. 3E. In the SW corner of intersection of Kessler Blvd. East Drive and North College Avenue 26.4 feet south of the center line of Kessler Avenue; 40.3 feet east of the center line of North College Avenue; 14.5 feet west of power pole; 12.3 feet east of center of manhole. In the NW corner of east-west curved sidewalk a chiseled cross. 725.874
DNR STA TT C2	In Marion County, Indianapolis West Quad, NE 1/4 Sec. 2, T.16N., R.3E. About 210' east of intersection of W. Kessler Blvd. and Fox Hill Drive; 23.2' north of the center line of Kessler; 5.0 feet SE of a light pole; 70.3 feet east of power pole #4 C-0-305B; 81.7 feet west of center line of drive; on the west end of drainage run off, a chiseled cross. 790.770
DNR STA TT C3	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 2, T.16N., R.3E. About 385 feet NE of the intersection of West Kessler Blvd. and 58th Street and Hoover Road: about 91 feet south of drive leading to Twin Oaks grounds (address 555) on the south east edge of Kessler Blvd.; 20.5 feet SE of center line of road; 38.2 feet NW of cyclone fence; 6.7 feet NW of a small tree; 71.3 feet SW of the S corner of the brick wall at the entrance to Twin Oaks; 55.4 feet NE of a tree. A one inch steel rod set in concrete about 0.2 feet below the ground. 771.803
DNR STA TT C4	In Marion County, Indianapolis West Quad, SW 1/4 Sec. 3, T.16N., R. 3E. Set on the south side of Kessler Blvd. and in line with the E. edge of Grandiose Drive: 17.6 feet S. of the center line of Kessler Blvd.; 23.0 feet SE of the center line intersection of Kessler Blvd. and Grandiose Drive; 41.7 feet S. of the S. edge of the wall on the north side of Kessler and the east edge of Grandiose Drive; 53.2 feet NW of 20 inch tree; 28.8 NE of a tree; 4.0 feet S. of edge of pavement. A 1 inch steel rod set in concrete about 0.2 feet below the ground. 772.819

MARION COUNTY
INDIANAPOLIS WEST QUAD

MARK

ELEVATION
FEET
(NGVD '29)

DNR STA TT C6	In Marion County, Indianapolis West Quad, near the SW corner of Section 15, T. 16N., R. 3E. At the intersection of 38th Street and Cold Spring Road and Knollton Road; at the West end of the median strip dividing 38th Street. On the east side of the intersection; 37.5 feet S. of the center line of west bound 38th Street; 23.3 feet north of the center line of east bound 38th Street and 0.4 feet west of the west edge of curbing of median. A chiseled cross. <div style="text-align: right;">750.493</div>
DNR STA TT C8	In Marion County, Indianapolis West Quad, SE 1/4 Sec. 14, T. 16N., R. 3E., At the intersection of 38th Street and Cornelius, at the west end of the median dividing 38th Street on the east side of the intersection, 20.5 feet S. of the center line of west bound 38th Street, 17.8 feet east of the center line of Cornelius, 26.5 feet NE of manhole cover, 49.5 feet SW of fire hydrant, 0.8 feet west of west edge of curb. A chiseled cross. <div style="text-align: right;">739.978</div>
DNR STA TT C7	In Marion County, Indianapolis West Quad, NE 1/4 Sec. 22, T. 16N., R. 3E. At the SW corner of the intersection of 38th Street and Northwestern Ave. (old U.S. Hwy. 421) at the west most corner of a traffic island: 19.9 feet south of the center line of east bound 38th Street; 42 feet west of a power pole on the traffic island; 64.2 feet east of a light pole; 68.0 feet northwest of a fence corner (cyclone fence) and 0.8 feet west of back of curb. A chiseled cross. <div style="text-align: right;">761.513</div>
DNR STA TT C10	In Marion County, Indianapolis West Quad, SE 1/4 Sec. 26, T. 16N., R. 3E. On the SW corner of the Illinois Street Bridge over Fall Creek: 14.6 feet west of the center line of Illinois Street; 10.9 feet SE of the S end of West guard rail; 30.0 feet NE of a power pole; 50.1 feet N of center of manhole cover; on the S end of the centerline of the sidewalk a chiseled cross. <div style="text-align: right;">717.490</div>

MARION COUNTY
INDIANAPOLIS WEST

MARK	ELEVATION FEET (NGVD 29)
DNR BM MAR 73 RESET	In Marion County, Indianapolis West Quad., SW 1/4 Sec 35, T. 17 N., R. 3 E., Near Broad Ripple, at the North Meridian Street bridge over White River, a vertical mark set in East side of the second concrete pier from the south end of bridge. 1.7 feet below a chiseled out scar where the original bench mark tablet had been set (the stem of the old mark is still in place), 0.4 feet North of the South edge of the pier, about flush with the ground, A standard Indiana Flood Control and Water Resources Commission bronze bench mark tablet, stamped "MAR 73 RESET" 710.698

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
NGS BM Q 64	In Marion County, Maywood Quad, SW 1/4 Sec. 15, T. 15N., R. 3E. At old southwest city limits of Indianapolis at Kentucky Avenue (old S.R. 67) on the concrete arch bridge over Eagle Creek, at 2200 South Belmont Avenue. Set in top of the north-east end of the southeast concrete railing, a standard USC & GS benchmark tablet stamped "Q 64 1946". 694.438
DNR BM MAR 23	In Marion County, Maywood Quad, SW 1/4 Sec. 22, T. 15N., R. 3E. On the Indianapolis Sewage Disposal Plant Grounds on S. Belmont Street, on the concrete walk at the north entrance to the Administration Building; 0.7 foot north of the north wall of the building; 6.0 feet east of the center of the doorway; level with the ground; a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 23". 691.782
DNR BM MAR 49 RESET	In Marion County, Maywood Quad, S 1/2 Sec. 14, T. 15N., R. 3E. At the Raymond Street bridge over White River, set in the top at the north end of the base of the 9th pier west from the east end of the bridge, 52 feet east from the center line of West Street, 19 feet north from the center line of Raymond Street, about 18 feet below the bridge floor, 6.4 feet above ground, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 49 RESET 1959". 689.386
DNR BM MAR 50	In Marion County, Maywood Quad, S 1/2 Sec. 14, T. 15N., R. 3E. On West Street 0.25 mile north of Raymond Street, at the Indianapolis Union Railroad Bridge over White River and West Street, on the south end of the southeast wingwall, 84 ft. south of the center line of the bridge, 32 feet east of the center line of West Street, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 50". 697.355
DNR TBM WR 201	In Marion County, Maywood Quad, about 6.5 miles east of Southport, 6.35 miles west along Southport Road (Union Street) from its intersection with State Road 431 in Southport to a northwest to southeast T-road (Mann Road), thence 0.5 mile generally north along Mann Road to a T-road west (Mills Road) and a 1 foot pipe culvert under Mann Road, set in the top at the center of the west headwall of the culvert, 24 feet north from the center line of Mills Road, 18 feet west from the center line of Mann Road, 1 foot above the roads, a chiseled square. 703.232

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 110	In Marion County, Maywood Quad, Near the NW corner of Sec. 17, T. 14N., R. 3E. About 6.0 miles west of Southport, 6.0 miles west along Southport Road (Union Street) from its intersection with Madison Ave. (old St.Rd. 431) at Southport to the Southport Road concrete bridge over the White River; set in the top at the east end of the south concrete sidewalk of the bridge; 16.0 feet south of the center line of the bridge; 10.5 feet west of the east end of the south sidewalk; 0.7 foot above the road; a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 110 1956". 676.901
DNR BM MAR 96	In Marion County, Maywood Quad, SE 1/4 Sec. 9, T. 14N., R. 3E. About 3.9 miles west of Southport, 3.9 miles west along Southport Road (Union Street) from its intersection with Madison Ave. (old S.R. 431) in Southport to the intersection of South Belmont Avenue, thence 0.2 mile north along S. Belmont Avenue to the S. Belmont Avenue concrete arch bridge over Little Buck Creek, set in the top of the south end of the west concrete guardrail, 13 feet west from the center line of the road, 5.1 feet north from the south end of the west guardrail, 3.7 feet above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 96 1956". 688.264
DNR BM MAR 97	In Marion County, Maywood Quad, S 1/2 Sec. 10, T. 14N., R. 3E. About 3.2 miles west of Southport, 3.3 miles west along Southport Road (Union Street) from its intersection with Madison Ave. (old S.R. 431) in Southport to the crossing of Harding Street, thence 0.15 mile north along Harding Street to the Harding Street concrete bridge over Little Buck Creek, set in the top of south end of the west concrete guardrail, 14 feet west from the center line of the road, 7 feet north from the south end of the west guardrail, 3 feet above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 97 1956". 687.735
DNR TBM LBC 3	In Marion County, Maywood Quad, SE 1/4 Sec. 10, T. 14N., R. 3E. About 2.8 miles west of Southport, 2.95 miles west along Southport Road (Union Street) from its intersection with Madison Ave. (old S.R. 431) in Southport to the crossing of the Indiana Rail Road (former Illinois Central RR), thence 0.25 mile north along the railroad to the Railroad bridge over Little Buck Creek, set in the top of the northwest end of the northeast abutment, 8 feet below the rails, 5.5 feet northwest of the northwest rail, 1 foot northeast of the southwest face of the northeast abutment, a chiseled triangle. 689.985

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
NGS BM A 14	In Marion County, Maywood Quad, NW 1/4 Sec. 11, T. 14N., R. 3E. About 2.7 miles west of Southport 2.0 miles northeast along Bluff Road from the old Standard Oil Service Station in Glenns Valley, at the Indiana Rail Road iron bridge overhead crossing of State Road 37, set in the top of the east concrete wingwall of the south abutment, 26 feet above the railroad tracks, 14 feet southeast from the center line of Bluff Rd., 1.9 feet south of the southeast end of the iron bridge, 0.4 foot above the road, a standard USC&GS benchmark tablet, stamped "A 14 1930". 726.960
DNR TBM HD 1	In Marion County, Maywood Quad, NW 1/4 Sec. 2, T. 14N., R. 3W. About 3.1 miles northwest of Southport, 2.1 miles northwest along State Road 431 from its intersection with Southport Road in Southport to Thompson Road, thence 2.0 miles generally west along Thompson Road to Bluff Road, in the southeast quarter of the intersection at the northeast corner of a 10 foot pipe culvert over Haueisen Ditch on Bluff Road, set in the top at the north end of the east headwall of the culvert, 23 feet east of the center line of Bluff Road, 21 feet south of the center line of Thompson Road, 0.75 foot south of the north end of the east headwall, 0.3 foot above the road, a chiseled triangle. 697.984
DNR BM MAR 155	In Marion County, Maywood Quad, NW 1/4 Sec. 35, T. 15N., R. 3E., about 2.5 miles northwest of Edgewood, 1.5 miles northwest along Madison Ave. from its intersection with Epler Ave. in Edgewood to Hanna Ave., thence 1.5 miles west along Hanna Ave. to Bluff Rd., thence 0.2 mile south along Bluff Rd. to a 60 foot concrete bridge over Lick Creek, set at the apex of the northeast wing- wall of the bridge, 18 feet east of the center line of Bluff Rd., 0.7 foot south of the north side of the northeast wingwall, 0.6 foot above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 155 1960". 695.825
DNR BM MAR 154	In Marion County, Maywood Quad, N 1/2 Sec. 26, T. 15 N., R. 3E. About 3 miles northwest of Edgewood, 0.2 mile northwest along Madison Avenue from its junction with U.S. Highway 31 to Troy Avenue, thence 0.95 mile west along Troy Avenue to Bluff Road, thence 0.22 mile south along Bluff Road to a 13 foot con- crete culvert over Highland Creek, in the northwest corner of the culvert, set in the top of the west headwall, 23 feet west of the center line of Bluff Road, 0.85 foot south of the north end of the west headwall, 0.2 foot above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 154 1960". 682.059

MARION COUNTY
MAYWOOD QUAD

ELEVATION
FEET
(NGVD '29)

MARK

DNR TBM
GC 1 In Marion County, Maywood Quad, SW 1/4 Sec. 23, T. 15N., R. 3E. About 2.1 miles east of Maywood, 0.2 mile northwest along Madison Avenue from its junction with U.S. Highway 31 to Troy Avenue, thence 1.45 miles west along Troy Avenue to the Indiana Rail Road, thence 0.1 mile north along the RR tracks to a wooden trestle over Germania Creek, at the southeast corner of the trestle on the south bridge seat, 5.8 feet east of the east rail of the tracks, 1.2 feet below the tracks, 0.2 foot south of the north face of the south bridge seat, a round bolt head, marked TBM GC 1. 683.334

DNR BM
MAR 153 In Marion County, Maywood Quad, S 1/2 Sec. 23, T. 15 N., R. 3E. About 3.2 miles northwest of Edgewood, 0.2 mile northwest along Madison Avenue from its junction with U.S. Highway 31 to Troy Avenue, thence 1.0 mile west along Troy Avenue to Bluff Road, thence 0.2 mile north along Bluff Road to an 8 foot box culvert over Germania Creek, at the northwest corner of the culvert, set in the top at the north end of the west headwall, 35 feet west of the center line of Bluff Road, 5.0 feet below the road, 0.9 foot south of the north end of the west headwall, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 153 1960". 687.751

DNR BM
MAR 152 In Marion County, Maywood Quad, SW 1/4 Sec. 23, T. 15N., R. 3E. About 2.2 miles east of Maywood, 0.2 mile northwest along Madison Avenue from its junction with U.S. Highway 31 to Troy Road, thence 1.45 miles west along Troy Road to the Indiana Rail Road tracks, thence 0.4 mile generally northeast along the tracks to an iron railroad bridge over Pleasant Run, in the northwest corner of the bridge, set in the top of the 3rd step from the top of the northeast bridge seat, 16 feet west of the west rail of the tracks, 7.3 feet below the tracks, 1.2 feet north of the south side of the northeast bridge seat, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 152 1960". 680.791

DNR BM
MAR 151 In Marion County, Maywood Quad, S 1/2 Sec. 23, T. 15N., R. 3E. About 3.3 miles northwest of Edgewood, 0.2 mile northwest along Madison Avenue from its junction with U.S. Highway 31 to Troy Road, thence 0.95 mile west along Troy Road to Bluff Road, thence 0.35 mile north along Bluff Road to a concrete arch bridge over Pleasant Run, in the southwest corner of the bridge, set in the top of the west guardrail, 21.5 feet west of the center line of Bluff Road, 14.7 feet north of the south end of the west guardrail, 2.8 feet above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 151 1960". 695.043

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR TBM PR 26	In Marion County, Maywood Quad, S 1/2 Sec. 23, T. 15N., R. 3E. About 3.3 miles northwest of Edgewood, 0.2 mile northwest along Madison Avenue from its junction with U.S. Highway 31 to Troy Road, thence 1.0 mile west along Troy Road to Bluff Road, thence 0.4 mile north along Bluff Road to a concrete arch bridge over Pleasant Run, in the southeast corner of the bridge, set in the top of the east headwall of the bridge, 22 feet east of the center line of Bluff Road, 0.2 foot north of the south end of the east headwall, about level with the road, a chiseled square. 692.431
DNR TBM PR 25	In Marion County, Maywood Quad, S 1/2 Sec. 23, T. 15N., R. 3E. About 3.3 miles northwest of Edgewood, 0.2 mile northwest along Madison Avenue from its junction with U.S. Highway 31 to Troy Road, thence 1.0 mile west along Troy Road to Bluff Road, thence 0.4 mile north along Bluff Road to a concrete arch bridge over Pleasant Run, in the northeast corner of the bridge, set in the top of the east guardrail, 22 feet east of the center line of Bluff Road, 2.8 feet above the road, at the northeast corner of the north end of the east guardrail, a chiseled square. 691.973
USGS RM 1	In Marion County, Maywood Quad, NW 1/4 Sec. 24, T. 15N., R. 3E. At Indianapolis, at the U.S. Highway 31 and Madison Avenue bridge over Pleasant Run, set in the east end of the headwall of a storm sewer near the southwest corner of the bridge, 67 feet west of the center line of the highway, 12 feet below the road, 0.4 foot south of the north side of the headwall of the sewer, a standard U.S.G.S. Gaging Station disc, unstamped 688.166
INDOT BM MAR G 45	In Marion County, Maywood Quad, NW 1/4 Sec. 24, T. 15N., R. 3E. At the U.S. Highway 31 and Madison Avenue bridge over Pleasant Run, in the southwest corner of the bridge, set in the top of the west headwall, 47 feet west of the center line of U.S. Highway 31, 4.4 feet north of the south end of the west guardrail, 1.0 foot above the road, a standard I.S.H.C. benchmark tablet, stamped "MAR G 45". 701.086
DNR TBM PR 22	In Marion County, Maywood Quad, N 1/2 Sec. 24, T. 15N., R. 3E. At the South East Street concrete bridge over Pleasant Run, set in the top at the north end of the west guardrail of the bridge, 32 feet west of the center line of East Street, 4 feet above the roadway, 0.75 foot south of the north end of the west guardrail, a chiseled triangle. 707.720

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 149	In Marion County, Maywood Quad, NE 1/4 Sec. 24, T. 15N., R. 3E. At the Garfield Park Drive concrete bridge over Pleasant Run, set in the top at the southeast end of the southwest guard-rail of the bridge, 25 feet southwest of the center line of the road, 4 feet above the roadway, 0.8 foot northwest of the southeast end of the guardrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 149 1960". 709.874
DNR TBM PR 21	In Marion County, Maywood Quad, NE 1/4 Sec. 24, T. 15N., R. 3E. At the Raymond Street bridge over Pleasant Run, set in the top of a 5 foot pipe culvert adjoining the Raymond Street bridge, 24 feet south of the center line of Raymond Street, 3.8 feet below the roadway, 2.3 feet south of the south headwall of the bridge, 0.35 foot west of the east end of the culvert headwall, a chiseled triangle. 706.056
DNR BM MAR 148	In Marion County, Maywood Quad, SE 1/4 Sec. 13, T. 15N., R. 3E. At the Indianapolis Union Railway bridge over Pleasant Run, at Beecher Street and Pleasant Run Parkway North Drive, set in the top at the northeast end of the northeast wingwall of the bridge, 15 feet north of the north rail of the tracks, 9 feet below the tracks, 0.85 foot southeast of the northwest side of the northeast wingwall, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 148 1960". 717.272
DNR TBM PR 27	In Marion County, Maywood Quad, SE 1/4 Sec. 13, T. 15N., R. 3E. At the intersection of Beecher Street and Pleasant Run Parkway North Drive, at the Beecher Street iron bridge over Pleasant Run, 22.5 feet north of the center line of Beecher Street, 0.7 foot north of the far west post of the north guard-rail, 0.6 foot west of the east edge of the northwest bridge abutment, a chiseled square. 712.588
DNR TBM PR 20	In Marion County, Maywood Quad, SE 1/4 Sec. 13, T. 15N., R. 3E. At the intersection of Beecher Street and Pleasant Run Parkway North Drive, at the Beecher Street iron bridge over Pleasant Run, set in the top at the north end of the east bridge seat, 23 feet north of the center line of the road, 4 feet below the roadway, 0.6 foot east of the west face of the east bridge seat, a chiseled triangle. 708.342
DNR TBM PR 19	In Marion County, Maywood Quad, NW 1/4 Sec. 18, T. 15N., R. 4E. At the intersection of Shelby Street and East Pleasant Run Parkway North Drive, at the Shelby Street bridge over Pleasant Run, set in the top at the northeast corner of the east sidewalk, 40 feet east of the center line of the road, 0.8 foot above the road, 0.3 foot north of the north end of the east guardrail, a chiseled square. 720.804

MARION COUNTY
MAYWOOD QUAD

ELEVATION
FEET
(NGVD '29)

MARK

DNR BM
MAR 145 In Marion County, Maywood Quad, NW 1/4 Sec. 18, T. 15N., R. 4E. At the intersection of South Spruce Street and Pleasant Run Parkway South Drive, at the Spruce Street bridge over Pleasant Run, set in the top of the southwest wingwall of the bridge, 24 feet west of the center line of Spruce Street, 2.1 feet west and 0.7 foot north of the south end of the west sidewalk railing, 0.7 foot above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 145 1960".
725.085

DNR TBM
LBC 18 In Marion County, Maywood Quad, NW 1/4 Sec. 18, T. 14N., R. 4E. About 0.45 mile west of Southport, 0.45 mile west along Southport Road from its intersection with Madison Avenue in Southport to the Southport Road 80 foot concrete bridge over Little Buck Creek, set in the top at the west end of the south concrete sidewalk, 18 feet south from the center line of the road, 3.5 feet south from the north edge of the south sidewalk, 0.8 foot above the road, 0.3 foot north from the bottom of the northwest corner of the south guardrail, a chiseled square.
744.065

TBM LBC
LBC 19 In Marion County, Maywood Quad, N 1/2 Sec. 18, T. 14N., R. 4E. About 0.25 mile west of Southport, 0.25 mile west along Southport Road from its intersection with Madison Avenue in Southport to the Southport Road 100 foot concrete bridge over Little Buck Creek, set in the top of the south concrete sidewalk at the bottom corner at the west face of the south guardrail, 18 feet south from the center line of the road, 3.5 feet south from the north face of the south sidewalk, 0.8 foot above the road, a chiseled square.
751.404

DNR BM
MAR 144 In Marion County, Maywood Quad, NE 1/4 Sec. 18, T. 15N., R. 4E. At Villa Avenue and Pleasant Run Parkway, North Drive, at the Villa Avenue bridge over Pleasant Run, set in the top of the west guardrail abutment, 18 feet west of the center line of Villa Ave., 27 feet south of the north end of the west guardrail of the bridge, 0.8 foot above the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 144 1960".
730.876

MARION COUNTY
MAYWOOD QUAD

ELEVATION
FEET
(NGVD '29)

MARK

DNR TBM
PR 17 In Marion County, Maywood Quad, NE 1/4 Sec. 18, T. 15N. At Villa Avenue and Pleasant Run Parkway, North Drive, at the Villa Avenue bridge over Pleasant Run, set in the top at the northeast corner of the east concrete guardrail of the bridge, 18.5 feet east of the center line of the road, 3.7 feet above the sidewalk, 0.2 foot south of the north end of the east guardrail of the bridge, a chiseled cross. 734.330

DNR BM
MAR 101 In Marion County, Maywood Quad, SE 1/4 Sec. 1, T. 14N., R. 3E. About 0.8 mile southwest of Edgewood, 0.55 mile southeast along Madison Ave. from it's intersection with Epler Avenue in Edgewood to the intersection of Stop 8 Road, thence 0.7 mile west along Stop 8 Road to the Stop 8 Road bridge over Little Buck Creek, (about 0.2 mile east of U.S. 31) set at the east end of the north concrete sidewalk of the bridge, 14 ft. north of the center line of the road, 0.9 foot above the road, 0.9 foot west of the east end of the north sidewalk, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 101 RESET 1960". 729.840

DNR TBM
A In Marion County, Maywood Quad, N 1/2 Sec. 18, T. 14N., R. 4E., about 0.25 mile west of Southport, 0.25 mile west along Union Street (Southport Road) from its intersection with State Road 431 in Southport to the Southport Road 100 foot concrete bridge over Little Buck Creek, set in the top near the east end of the south concrete sidewalk of the bridge, 17.5 feet south of the center line of the road, 4.3 feet east of the east face of the south concrete guardrail, 0.8 foot above the roadway, 0.4 foot north of the south face of the south concrete sidewalk, a chiseled cross. 751.260

DNR TBM
B In Marion County, Maywood Quad, S 1/2 Sec. 7, T. 14N., R. 4E. About 0.3 miles west of Southport, 0.3 miles west along Southport Road from its intersection with Madison Ave. in Southport to the Southport Road 100 foot concrete bridge over Little Buck Creek, set in the top near the east end of the north concrete sidewalk of the bridge, 25.8 feet west of the east face of the north concrete guardrail, 14.5 feet north of the centerline of the road, 0.8 foot above the roadway, 0.3 feet north of the south face of the north concrete curbing, a chiseled cross. 751.144

INDOT BM
MAR G 98 In Marion County, Maywood Quad, SE 1/4 Sec. 7, T. 14N., R. 4E. At the Madison Avenue 3 span concrete bridge over Little Buck Creek, set in the top of the south end of the west concrete sidewalk of the bridge, 16 feet west of the center line of the highway, 0.8 foot above the roadway, 0.4 foot north of the south face of the west concrete guardrail, 0.2 foot east of the east face of the west concrete guardrail, a standard ISHC benchmark tablet, stamped "MAR G 98" 753.021

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
USGS BM 114 M	In Marion County, Maywood Quad, SW 1/4 Sec. 18, T. 14N., R. 3E. About 2.5 miles northeast of Landersdale, 3.0 miles generally northeast along Mann Road from the crossroad at Landersdale to the residence of A. Standish, set in the top of a concrete post, 87.0 feet northwest of the mailbox, 24.0 feet west of the center line of Mann Road, 10.0 feet south of the center line of a lane east, 2.5 feet south of a power pole (#5-776), 1.5 feet below the road, level with the ground, a standard USGS bronze disk, stamped "114 M 1945". 705.794
DNR TBM WHR 209	In Marion County, Maywood Quad, near the center of section 18, T 14N., R. 3E. About 2.8 miles northeast of Landersdale, 3.4 miles generally northeast along Mann Road from the crossroad at Landersdale to the concrete headwall of a 24 inch pipe culvert under the road, set in the top of the west headwall of the culvert, 18.0 feet north of the center line of a farm lane east, 15.5 feet west of the center line of Mann Road, 1.5 feet above the road, 0.5 foot south of the north edge of the headwall, 0.5 foot east of the west edge of the headwall, a chiseled cross. 698.804
DNR TBM WHR 211	In Marion County, Maywood Quad, NE 1/4 Sec. 18, T. 14N., R. 3E. About 5.95 miles west of Southport, 6.0 miles west along Southport Road from its intersection with Madison Avenue at Southport to the Southport Road bridge over the White River, set in the top at the west end of the south concrete sidewalk of the bridge, 53.7 feet northeast of the southwest edge of the south-west metal guardrail, 16.0 feet south of the center line of the road, 1.6 feet above the road, 1.4 feet north of the north edge of the south concrete guardrail, 0.4 foot south of the north edge of the south sidewalk, next to the dedication plaque on the bridge, a chiseled square. 690.288
DNR STA LI TT A7	In Marion County, Maywood Quad, SW 1/4 Sec. 35, T. 15N., R. 3E. In the median strip of I-465, just West of the Bluff Rd. underpass: 189.4 feet west of the west most I beam of the north guard rail of the east bound lane of the overpass over Bluff Road; 8.7 feet north of the north edge of the driving lane of east bound I-465 (not asphalt shoulder); on line with curb inlets on the north and south sides of the highway. A standard IDNR Div. of Water control station tablet in a concrete post stamped "LI TT A7". 720.911
DNR STA LI TT A8	In Marion County, Maywood Quad, NE 1/4 Sec. 35, T. 15N., R. 3E. About 0.7 miles west along I-465 from it's interchange with US Hwy. 31, and about 875 feet west of west end of it's bridge over Meridian Street; 32.5 feet west a speed limit sign; 2.1 feet north of the north edge of the shoulder; 78.4 feet north-east of "Sta. 88" stamped in pavement; 26.2 feet northwest of stamped "Sta. 87" stamped in pavement. A standard IDNR Div. of Water control station tablet in a concrete post stamped "LI TT A8". 715.300

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR STA LI TT A9	In Marion County, Maywood Quad, SE 1/4 Sec. 36, T. 15N., R. 3E. On the S. side of the east bound entrance ramp from north bound U.S. 31 to east bound I-465: about 0.2 miles northeast along the ramp from its junction with U.S. 31; about 2 feet northeast of the 20th I beam of guard rail from the southwest end of guard rail, 5.6 feet northwest of the northwest face of guard rail, 3.6 feet southeast of the southeast edge of the entrance ramp. A standard IDNR Div. of Water control station tablet in a concrete post stamped "LI TT A9". 732.012
DNR BM LBI 4 A	In Marion County, Maywood Quad, SW 1/4 Sec. 7, T. 14N., R. 4E. About 0.2 miles west on Southport Rd. from it's intersection with Madison Avenue in Southport, at the southeast corner of the Homecroft School yard, 38 feet north of Southport Road, 17.00 feet northeast of cut "X" in north edge of manhole rim, 4.99 feet southwest of southeast corner post of chain link fence, 54.51 feet westerly of a P.K. on south side of power pole nail 1 foot above the ground and on the east side of Buckridge West Drive. A standard IDNR Div. of Water control station tablet in a concrete post stamped "LBI 4 A". 748.949
DNR STA LBI 8 A	In Marion County, Maywood Quad, SW 1/4 Sec. 12, T. 14N., R. 3E. About 0.2 miles northwest along U.S. 31 from it's intersection of Southport Road, and about 150 feet southeast of the entrance to the "Les Caribe" Apartments, 68.85 feet southwest of a standard IDNR bronze disk stamped "REF 2 LBI 8 A" (Note: "REF 2 LBI 8 A" is located in the grass median of U.S. 31 on the approximate center line), 98.56 feet southeast of a standard IDNR bronze disk stamped "REF 1 LBI 8 A", 63.67 feet east of the northeast corner post of a chain link fence. A standard IDNR Div. of Water control station tablet in a concrete post stamped "LBI 8 A". 740.147
DNR STA LBI 11 A	In Marion County, Maywood Quad, SW 1/4 Sec. 1, T. 14N., R. 3E. About 300 feet west of U.S. 31 on Edgewood Ave., in the northeast corner of the intersection of Ransdell Street and Edgewood Avenue, 57.00 feet east of a P.K. nail in the south side of a power pole in northwest corner of intersection, 60.82 feet northwest of a P.K. nail in the east side of 36 inch Maple tree on south side of Edgewood Avenue, 2.02 feet southwest of a P.K. nail in power pole #239-726, A standard IDNR Div. of Water control station tablet in a concrete post stamped "LBI 11 A". 734.188
DNR STA LBI 14 A	In Marion County, Maywood Quad, near the center of Section 11, T. 14N., R. 3E. About 150 feet west along Banta Road from its intersection with Woodwind Drive, on the north side of Banta Road, just east of a chain link fence, 21.66 feet southeast of a P.K. nail in the south side of a 12 inch tree on the west side of a chain link fence, 34.89 feet southeast of a P.K. nail in the east side of a power pole on the west side of the fence, 3.21 feet northeast of the south end post of the chain link fence. Set in a concrete post a standard IDNR bronze control station tablet stamped "LBI 14 A". 722.652

MARION COUNTY
MAYWOOD QUAD

ELEVATION
FEET
(NGVD '29)

MARK

DNR STA In Marion County, Maywood Quad, NW 1/4 Sec. 15, T. 14N., R.
WRSI TT 14A 3E. About 0.35 miles south along S.R. 37 from its intersection
with Southport Road, on the east side of S.R. 37; about 500 feet
north of Belmont Road; 5.3 feet west of a R/W fence post. A
standard IFC&WRC control station tablet in a concrete post
stamped "WRSI TT 14A" 677.260

DNR BM In Marion County, Maywood Quad, W 1/2 Sec. 10, T. 14N., R.
WRSI TT 13A 3E. At the intersection of S.R. 37 and Banta Road, 62.5 feet
west of the centerline of south bound S.R. 37, 35.5 feet north
of the centerline of Banta Road, 5.73 feet SE of a P.K. nail and
cap in power pole #125 722, 3.02 feet NE of the right of way
fence. A standard IFC&WRC control station tablet in a concrete
post stamped "WRSI TT 13A" 677.846

DNR STA In Marion County, Maywood Quad, NW 1/4 Sec. 3, T. 14N., R.
WRSI TT 11A 3E. At the intersection of S.R. 37 and Epler Avenue, 75 feet
south of the center line of Epler Avenue, 49 feet southeast of
the center line of north bound S.R. 37, 38.62 feet south of a
P.K. nail and cap in power pole, 44.79 feet west of a P.K. nail
and cap in power pole, 29.83 feet north of a P.K. nail and cap
in power pole, 2.5 feet west of the right of way fence. A stan-
dard IFC&WRC control station tablet in a concrete post stamped
"WRSI TT 11A". 676.120

DNR STA In Marion County, Maywood Quad, SW 1/4 Sec. 34, T. 15N., R.
WHSI TT 9A 3E. In the median of I-465 about 175 feet west of the center
line S.R. 37 (Harding Street); 39 feet south of centerline of
the west bound lane; 20.1 feet south of a P.K. nail and cap on
edge of pavement; 17.2 feet northwest of another P.K. nail and
cap on edge of pavement; 16.75 northeast of another P.K. nail
and cap on edge of pavement. A standard IFC&WRC control station
tablet in a concrete post stamped "WHSI TT 9A". 697.302

DNR STA In Marion County, Maywood Quad, SE 1/4 Sec. 32, T. 15N., R.
WHSI TT 6A 3E. In the median of I-465, at the west end of it's bridge over
White River. 5.60 feet northwest of cut "X" in the northwest
wingwall of east bound I-465 bridge over White River. 6.8 feet
northeast of cut "X" in top of guard rail post at northwest
corner of the bridge. 4.86 feet south of southern most sign
post of sign. A standard IFC&WRC control station tablet in a
concrete post stamped "WHSI TT 6A". 686.053

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR STA WHSI TT 6C	In Marion County, Maywood Quad, W 1/2 Sec. 21, T. 15N., R. 3E. About 0.75 miles southwest of the intersection of Kentucky Ave. (Old S.R. 67) and Raymond Street, on the southeast side of the road; 82 feet southwest of the entrance to "Capitol Builders Inc. Model Homes" on the southeast side of S.R. 67; 53 feet southeast of the center line of S.R. 67; 35.0 feet northwest of a P.K. nail and cap in power pole (107 630); 75.42 feet northwest of a P.K. Nail in cap on the southern most sign post of "Model Homes - Capital Builder's Sign; 72.40 feet southwest of P.K. nail and cap in northern most post of "Model Homes - Capital Builder's sign. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 6C". 687.432
DNR STA WHSI TT 10C	In Marion County, Maywood Quad, S 1/2 Sec. 22, T. 15N., R. 3E. At the southwest corner of the Harding Street bridge over White River, 12.0 feet south of the bridge, 28.3 feet west of the center line of Harding Street, 6.15 feet southwest of an ISHC BM tablet, 5.72 feet west of the guard rail post at the south end of bridge. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 10C". 691.996
DNR STA WHSI TT 2D	In Marion County, Maywood Quad, N 1/2 Sec. 15, T. 15N., R. 3E. In the southeast corner of the intersection of Howard and Harding Streets, 22.7 feet east of the center line of Harding Street, 52.6 feet south of the center line of Howard Street, 6.5 feet west of the west edge of a five foot concrete walk, 29.98 feet southwest of a P.K. Nail and cap in power pole, 2.93 feet northwest of the northwest corner of a concrete wall. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 2D". 689.067
DNR STA WHSI TT 14D	In Marion County, Maywood Quad, center Sec. 23, T. 15N., R. 3E. At the southeast corner of the intersection of Bluff Road and West Street; 294 feet south of the center line of Bluff Road; 21 feet east of the centerline of Bluff Road; 2.9 feet west of a steel fence post of a fence around "Holy Cross Cemetery"; 56.00 feet south of a P.K. and cap in power pole; 11.85 north of a P.K. Nail and cap in a 12 inch Elm Tree. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 14D". 687.422
DNR STA WHSI TT 21E	In Marion County, Maywood Quad, NW 1/4 Sec. 18, T. 14N., R. 3E. About 0.4 miles south on Mann Rd. from it's intersection with Southport Rd., 19 feet west of the center line of Mann Road and in line with the extended center line of the driveway at 7407 Mann Road; 64.80 feet southeast of a P.K. Nail and cap in power pole #2-746; 56.12 feet southwest of a P.K. Nail and cap in power pole #65-746; 36.35 feet northwest of a P.K. Nail and cap in mail box post. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 6C". 695.203

MARION COUNTY
MAYWOOD QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR STA WHSI TT 24E	In Marion County, Maywood Quad, W 1/2 Sec. 7, T. 14N., R. 3E., At the intersection of Mann Road and Mills Road, 20 feet west of the center line of Mann Road, 58 feet south of the center line of Mills Road in front of "6510" Mann Road, 46.35 feet north- west of a P.K. nail and cap in power pole #53 746, 23.53 feet northeast of a P.K. nail and cap in power pole #54 746, 12.10 feet southeast of a P.K. nail and cap in a 10 inch Locust Tree. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 24E". 703.113
DNR STA WHSI TT 26E	In Marion County, Maywood Quad, N 1/2 Sec. 7, T. 14N., R. 3E., From the intersection of Southport Road and Mann Road, travel north on Mann Road about 0.9 miles to an east west fence line on the east side of the road thence 751 feet east along said fence line to the mark; 1.5 feet south of the fence line, 6.48 south- east of a P.K. nail and cap in fence post, 10.85 feet southwest of a P.K. nail and cap in fence post. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 26E". 703.612
USGS BM 116 M	In Marion County, Maywood Quad, SW 1/4 Sec. 6, T. 14N., R. 3E. At the intersection of Mann Road and Epler Avenue, 15 feet north of the extended center line of Epler Avenue, 20 feet east of the center line of Mann Road, 2 feet west of a woven wire fence, 50.40 feet southeast of a P.K. nail and cap in power pole, 55.94 feet northeast of a cut "X" in the northwest corner of the headwall at the southwest corner of the intersection, 34.46 northwest of a P.K. nail and cap in fence post. A stan- dard USGS benchmark tablet in a concrete post stamped "116 M 1945 722". 721.634
DNR BM WHSI TT 2F	In Marion County, Maywood Quad, NE 1/4 of Sec. 18, T. 14N., R. 3E. About 1.8 miles west along Southport Road from its in- tersection with S.R. 37, to the mark on the south side of the road; 18.5 feet south of the centerline of Southport Road; 15.8 feet west of a power pole; 106 feet west of the center line of the driveway to the residence at 3925 Southport Road; and about flush with the ground. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 2F". 660.092
USGS BM 113 M	In Marion County, Maywood Quad, near the NE Corner of Sec. 16, T. 14N., R. 3E. About one mile west of S.R. 37 along South- port Road at the Intersection of Southport Road and S. Tibbs Avenue. About 30 feet south of the center line of Southport Road; 3.9 ft. NE of a power pole; and 2 feet west of a fence corner. A standard USGS benchmark tablet stamped "113 M 1945 665". 665.002

MARION COUNTY
MAYWOOD QUAD

MARK		ELEVATION FEET (NGVD '29)
DNR STA	In Marion County, Maywood Quad, SE 1/4 Sec. 20, T. 14 N.,	
WHSI TT 2G	R. 3E. About 0.4 mile southwest along Bluff Road from Glenns Valley to Wicker Road, thence 0.9 mile west on Wicker Road to a "T" road north (Lake Road), and the mark in the northwest quadrant of the intersection; 12 feet north of the center line of Wicker Road; 43 feet west of the centerline of Lake Road; 40.5 feet northwest and across the road from a power pole. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 26".	657.343
DNR STA	In Marion County, Maywood Quad, in the SW of 1/4 Section 29,	
WHSI TT 1N	T. 15N., R. 3E. . About 0.6 miles south along Foltz Road from its intersection with Kentucky Avenue to its intersection with Standish Drive, and the mark in the southwest corner of the intersection; 23 feet west of the center line of Foltz Road; 41.5 feet south of the center line of Standish Drive; 51.2 feet northeast of power pole number 35 658; 44.0 feet northwest of and across the road from another power pole; 65.3 feet southwest of and across the road from an apple tree. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 1N"	689.810
DNR STA	In Marion County, Maywood Quad, in the SW of 1/4 Sec. 32, T.	
WHSI TT 3N	15N., R. 3E., 2nd. P.M. About 1.5 miles south along Foltz Road from its intersection with Kentucky Avenue to its intersection with Gambel Road. In the Southeast corner of the intersection; 16 feet east of the center line of Foltz Road; 104 feet south of the center line of Gambel Road; across the road from 4644 Gambel Road; 29.5 feet east of and across the road from a mailbox; 30.2 feet north of power pole number 34.688; 70.0 feet northeast from power pole 23.688. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 3N"	671.424
DNR STA	In Marion County, Maywood Quad, in the NE of 1/4 Section 29,	
WHSI TT 3P	T. 29N., R. 3E., 2nd P.M. About 0.6 miles south along Tibbs Avenue from its intersection with Kentucky Avenue to its intersection with Murry Street. In the southeast corner of the intersection; 33 feet west of the center line of Tibbs Avenue; 28 feet south of the center line of Murry Street; 14.5 feet southeast of a sign post; 80.1 feet northwest of a mailbox; 50.5 feet southeast of and across the road from a signpost. A standard IFC&WRC control station tablet in a concrete post stamped "WHSI TT 3P"	684.402

MARION COUNTY
MCCORDSVILLE QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR BM MAR 92	In Marion County, McCordsville Quad, SE 1/4 Sec. 21, T. 17N., R. 5E. About 1.7 miles northwest of Oaklandon, 2.20 miles north along Oaklandon Road and Germantown Road from its junction with State Road 67 south of Oaklandon to a T road west (Fox Road), thence 0.3 mile west along Fox Road to a 24 foot box culvert under the road, set in the top of the southeast concrete wingwall of the culvert, 35 feet south from the center line of the road, 7 feet below the road 0.3 foot south from south face of wingwall, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 92 1956". 794.701
DNR BM MAR 93	In Marion County, McCordsville Quad, SW 1/4 Sec. 15, T. 17N., R. 5E. About 2.5 miles north of Oaklandon, 2.90 miles north along Oaklandon Road and Germantown Road from Oaklandon Road junction with State Road 67 south of Oaklandon to a right angle turn east, (86th St.), thence 0.25 mile east along 86th Street to an 18 foot box culvert under the road, set in the top of the northeast concrete wingwall, 11 feet north from the center line of the road, 0.8 foot east from the east end of the north headwall, 0.5 foot below the road, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 93 1956". 798.546
DNR BM MAR 91	In Marion County, McCordsville Quad, NW 1/4 Sec. 20, T. 17N., R 5E., at Geist Reservoir, set in the top of concrete curbing for spillway wall, 450 feet southeast from northwest end of the dam, 14 feet above the concrete spillway, 11.5 feet northeast from the top step of a set of steps leading down the levee, 0.7 foot above the top of levee, a standard Indiana Flood Control and Water Resources Commission benchmark tablet, Stamped "MAR 91, 1956". 798.621
DNR STA FIE E6	In Marion County, McCordsville Quad, E1/2 Sec. 31, T. 17N., R. 5E. About 2.0 miles west of Oaklandon, at Fort Benjamin Harrison, 1.5 miles north along Lee Road from its intersection with East 56th Street to the entrance to the VFW Post No. 7119, set in the top of a concrete post, 43.3 feet south from the center line of driveway leading east to the VFW Post, 21.8 east from the center line of Lee Road, 11.3 feet east from east edge of pavement of Lee Road, 0.2 foot above ground, a standard Indiana Department of Natural Resources benchmark tablet, stamped "FIE E 6". 834.994
DNR STA FIE F2	In Marion County, McCordsville Quad, NW 1/4 Sec. 32, T. 17N., R. 5E., about 1.7 miles west of Oaklandon, 0.2 mile north along Winona Drive, from its junction with 63rd Street, set in the top of a concrete post, 80 feet south from south edge of driveway to residence 6630 Winona Drive, 31.0 feet north from north edge to driveway to residence 6622 Winona Drive, 23.7 feet west from the center line of Winona Drive, 0.1 foot above ground, a standard Indiana Department of Natural Resources benchmark tablet stamped "FIE F 2". 841.536

MARION COUNTY
ZIONSVILLE QUAD

MARK	ELEVATION FEET (NGVD '29)
DNR TBM E 6	In Marion County, Zionsville Quad, S 1/2 Sec. 15, T. 17N., R. 2E. On 86th Street (old State Road 100), at it's intersection with Moore Road, 1.25 miles east of the intersection of 86th. Street with U.S. Highway 52, 45 feet north of the center line of 86th. Street, 30 feet east of the center line of Moore Road, on the north concrete headwall of an 18 inch concrete pipe culvert under 86th. Street, level with the roadway of 86th. Street. A chiseled square. 836.411
INDOT BM MAR G 26	In Marion County, Zionsville Quad, S 1/2 Sec. 15, T. 17N., R. 2E. On 86th Street (old State Road 100) 2.2 miles east from U.S. Highway 52, on a concrete arch bridge over Eagle Creek, 0.5 foot south of the north handrail, 10 feet east of the west end of the north handrail, a standard "State Highway Commission of Indiana" bronze benchmark tablet stamped "MAR G 26". 823.646
DNR BM MAR 2 RESET	In Marion County, Zionsville Quad, NW 1/4 Sec. 27, T.17N., R.2E. From Traders Point 0.4 mile north along Lafayette Rd., thence 0.1 mile northeast along Moore Road, thence 0.5 mile east along 79th Street, thence 0.15 mile south along a paved road to a 15 foot concrete bridge over a small stream, set in the top at the north end of the east concrete guardrail of the bridge, 10 feet east of the center line of the road, 3.3 feet above the roadway, 1.5 feet south of the north end of the east guardrail, a standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet, stamped "MAR 2 RESET 1962". 802.028
DNR BM MAR 3	In Marion County, Zionsville Quad, E. 1/2 Sec. 28, T.17N., R.2E. At Traders Point at the Lafayette Road Bridge over Eagle Creek, on the southwest walkway at the northwest end, 0.9 foot above the roadway. A standard Indiana Flood Control and Water Resources Commission bronze benchmark tablet stamped "MAR 3". 800.957

IFC&WRC BM UNSTAMPED

In Marion County, Maywood Quad., NW $\frac{1}{4}$ of section 29, T. 15 N., R. 3 E., 2nd P. M. Set in Indianapolis in Mars Hills. Set in the Mooresville Road bridge over State Ditch. Set in top of the East end of the north concrete sidewalk. An IFC & WRC BM Tablet "not stamped".
3rd Order 694.872 feet NGVD 1929

IDNR BM PRC 100 2002

In Marion County, Beech Grove Quad., set in the NW $\frac{1}{4}$ of section 22, T. 14 N., R. 4 E., 2nd P. M. 2.0 miles northeast of north edge of Greenwood, Indiana. Set in the SW $\frac{1}{4}$ of Stop 11 Road overpass over I-65. Set in the west Right-of Way of south bound lane of I 65. \pm 215 feet south of the Stop 11 over Pass, 215 feet northeast of the northeast corner of black chain link fence, 62 feet west of the west edge of south bound lane of I 65, 51.5 feet west of concrete outlet pipe by interstate, 3 feet east of Right-of-Way fence, about level with the ground. Set in the top of a concrete post. An INDIANA DEPARTMENT OF NATURAL RESOURCES bench mark tablet stamped "PRC 100 2002"
2nd Order 828.320 feet NGVD 1929

IDOT BM 1 2002

In Marion County, Beech Grove Quad., set in the S $\frac{1}{2}$ of section 20, T. 14 N., R. 4 E., 2nd P. M. Set near north side of Greenwood, Indiana. Set in the NE $\frac{1}{4}$ of the intersection of County Line Road and Conrail Railroad. Set on top of a concrete retaining for drainage pipe, set at the "V" point of retaining wall. 48 feet east of the centerline of railroad tracks, 18.8 feet north of north curb of County Line Road, 6 feet northeast of railroad crossing post with lights attached, about 2 feet below the road. An INDIANA DEPARTMENT OF TRANSPORTATION bench mark tablet stamped "1"
2nd Order 793.298 feet NGVD 1929

IDOT BM 2 2002

In Johnson County, Beech Grove Quad., set in the NW $\frac{1}{4}$ of section 29, T. 14 N., R. 4 E., 2nd P. M. Set near north side of Greenwood, Indiana. Set in the southeast concrete bridge abutment of the County Line Bridge over Pleasant Run Creek. 3.5 feet northeast of south face of abutment, 0.7 feet south of south face of concrete guardrail, 0.5 foot west of the east face of concrete abutment, about 1.8 feet above the road. An INDIANA DEPARTMENT OF TRANSPORTATION bench mark tablet stamped "2"
2nd Order 781.156 feet NGVD 1929

IDNR TBM TRIANGLE 1989

In Marion County, Beech Grove Quad., set in the SE $\frac{1}{4}$ of section 21, T. 14 N., R. 4 E., 2nd P. M. About 0.3 miles north of the Marion Johnson County Line Road. Set on top of the north end of the east concrete guardrail of the Sherman road bridge over Pleasant Run Creek. A chiseled Triangle.

2nd Order 795.285 feet NGVD 1929